
AUDIO-VIDEO STEREO RECEIVER

KR-694/V5560/V6060 SERVICE MANUAL

KENWOOD

© 1994-1 PRINTED IN JAPAN B51-4842-00(S) 3457


KR-V5560(KR-694 sames as KR-V5560 without Model name.)



KR-694/V5560/V6060 CONTENTS


ACCESSORIES 2	WIRING DIAGRAM	23
REMOTE CONTROL UNIT 5	PC BOARD(Component side view)	25
DISASSEMBLY FOR REPAIR 8	SCHEMATIC DIAGRAM	33
BLOCK DIAGRAM 9	EXPLODED VIEW	49
CIRCUIT DESCRIPTION11	PARTS LIST	51
ADJUSTMENT20	SPECIFICATIONS	62


ACCESSORIES



KR-694/V5560/V6060

KR-V6060 M type (Except E,T type)






^{*}Refer to parts list on page 51.


KR-694/V5560/V6060

KR-V6060(E,T Type)




KR-694/V5560/V6060 REMOTE CONTROL UNIT

KR-694/V5560




KR-694/V5560/V6060 REMOTE CONTROL UNIT

KR-V6060 (Except E,T type)



KR-694/V5560/V6060 REMOT CONTROL UNIT

KR-V6060 (E,T type)




KR-694/V5560/V6060 DISASSEMBLY FOR REPAIR

Remove the upper case in advance.

1. How to remove the front panel

Remove the four screws (1) at the bottom of the front panel and the volume knob and nut. Remove the panel forward while removing the Balance knob (2) the left

and right tabs (3).




2. How to remove the main circuit board (with the front panel attached)


Remove the Volume knob and nut, and the Balance knob (②). Next remove the 16 screws (③) and remove the main PCB from the main chassis.

When removing, lift up the main PCB, move it right, lift it up in direction (②) while being careful not to contact the transformer PCB, and stand it up as shown in the diagram below.

If the main PCB is unstable, insert a spacer (3) as needed near the PHONES jack.



KR-694/V5560/V6060 KR-694/V5560/V6060 BLOCK DIAGRAM



1. Function description

TUNER

	KR-694	KR-V5560	KR-V6060	KR-V7060	KR-V8060
20 ch RANDOM PRESET	0	0	0	0	0
Tuning control by IF count	0	0	0	0	0
Direct selection	0	0		0	0
RDS function (E, T type only)			0	0	


O: FUNCTION NO mark: NO FUNCTIOIN

AMP

		KR-694	KR-V5560	KR-V6060	KR-V7060	KR-V8060
1 INPUT SELECTOR TAPE 2 ON TAPE 2 OFF CD TUNER PHONO TAPE 1 VIDEO 1 VIDEO 2		0	0	0	0	0
② VIDEO SELECTOR VIDEO 1 VIDEO 2		0	0	0	0	0
3 L	INE STRAIGHT	0	0	0	0	
OZCOBBC® (PRO LOGIC(NOR, WIDE, PHANTOM) 3 STEREO	0	0	0	0	0
כנגס	THEATER LOGIC			0	0	
MOOK 02C(DSP LOGIC DSP (ARENA,					0
(5) S	SURROUND MEMORY (M1 ~ M4) SURROUND MODE CENTER MODE DELAY TIME CENTER LEVEL			(E, T type only)	(E, T type only)	
6 S	PEAKER A/B SELECT	0	0	0	0	0
⑦ IMPEADANC SELECTOR (4/8Ω)				(AUTO)	(MANUAL)	O (MANUAL)

O: FUNCTION No Mark: NO FUNCTION

*? INPEDANCE SELECTOR (4/8 Ω)



AUTO (KR-V6060 only)

Speaker IMPEDANCE SELECTOR

Set the IMPEDANCE SELECTOR switch on the rear panel according to the impedance of the front speakers used. The center and rear speakers should have impedances from 8 to 16 ohms regardless of the position of this switch.

For surro	und play	For non-surround play			
Front speaker impedance	Selector position	Front speaker impedance	Selector position		
A or B speakers $4\Omega \sim 6\Omega$	LESS THAN 8Ω A BΩ OR MORE Y MPEDANCE SELECTOR	A or B speakers $4\Omega \sim 6\Omega$	LESS THAN 8Ω A BΩ OR MORE VI MPEDANCE SELECTOR		
A or B speakers $8\Omega \sim 16\Omega$	LESS THAN 8Ω A S S S S S S S S S S S S S S S S S S	A or B speakers $8\Omega\sim16\Omega$ A and B speakers $8\Omega\sim16\Omega$	LESS THAN 8Ω A B B OR MORE THE BELECTOR		

- It is not possible to use both A and B speaker systems for surround play.
- It is not possible to use both A and B speaker systems if speakers have impedances from 4 ohms to 6 ohms.

2. Conditions according to the destination and model

TUNER

	DIODE SW							Reference	
Destination	DSW2 D33	DSW1 D34	DSW0 D35	BAND	BAND Receiving Remarks		IF	Frequency	
K1				FM	87.5 MHz~108.0 MHz	100 kHz	+ 10.7 MHz	50 kHz	
(1700)	0	0	0	AM	530 kHz~1700 kHz	10 kHz	+ 450 kHz	10 kHz	
K2	1 0 1				FM	87.5 MHz ~ 108.0 MHz	100 kHz	+ 10.7 MHz	50 kHz
(1610)		0	1	AM	530 kHz ~ 1610 kHz	10 kHz	+ 450 kHz	10 kHz	
	0	0 1	1	FM	87.5 MHz~108.0 MHz	50 kHz	+ 10.7 MHz	50 kHz	
E1				AM	531 kHz~1602 kHz	9 kHz	+ 450 kHz	9 kHz	
E3			_	FM	87.5 MHz~108.0 MHz	50 kHz	+ 10.7 MHz	50 kHz	
(RDS)	1	1 0	1	AM	531 kHz ~ 1602 kHz	9 kHz	+ 450 kHz	9 kHz	
М	0	х	1	K2/E1 changes by only setting "DSW1". (DSW1 = 0: K2 Type, 1: E1 type)					

^{*} DIODE SW (DSWX): 0 = Without DIODE (when static, input LOW)

1 = With DIODE (when static, input HIGH)

X = TRANSISTOR SW (0 = OFF 1 = ON)

AMP

MODEL	DIODE SW	DSW 4	DSW 3	Surround function	IMPEDANCE SELECTOR (4/8Ω)	
MODEL	Ref. No.	D31	D32	Surround function	IMPEDANCE SELECTOR (470)	
KR-694/V5560		0	0	PRO-LOGIC, 3 STEREO		
KR-V6060		0	1	PRO-LOGIC, 3 STEREO, THEATER LOGIC	AUTO	
KR-V7060		1	0	PRO-LOGIC, 3 STEREO, THEATER LOGIC	MANUAL	
KR-V8060		1	1	PRO-LOGIC, 3 STEREO, DSP LOGIC, DSP.	MANUAL	

0: NO DIODE 1: ADD DIODE

KR-694/V5560/V6060

CIRCUIT DESCRIPTION

3. Function initial setting

- 1 POWER OFF
- (2) AMP system

• AUDIO SELECTOR **TUNER** • IMAGE SELECTOR VIDEO 1 SPEAKER A ON SPEAKER B **OFF** • TAPE 2 MONITOR **OFF** LINE STRAIGHT OFF

3 TUNER system

• LOUDNESS

• BAND FM FREQUENCY Lower limit of FM (87.5 MHz) • TUNING MODE **AUTO TUNING** (AUTO STEREO)

OFF

---ch

-4 dB

4 SURROUND system

. P. CH DISPLAY

- MODE BYPASS (OFF)
- CENTER LEVEL 0 dB
- REAR LEVEL 0 dB
- PROLOGIC MODE **NORMAL**
- 3 STEREO MODE **NORMAL**
- DSP MODE **ARENA**
- PRESENCE LEVEL:

THEATER LOGIC

-0 dBDSP DSP LOGIC (KR-V8060 ONLY) -0 dB

• DELAY TIME: DOLBY PROLOGIC 20 ms DSP 30 ms DSP LOGIC (KR-V8060 ONLY) 40 ms THEATER LOGIC 30 ms

(5) TEST PRESET FREQUENCY

	K1 TYPE	K2 TYPE	E TYPE
01 ch	FM 98.00 MHz	FM 98.00 MHz	FM 98.00 MHz
02 ch	FM 108.00 MHz	FM 108.00 MHz	FM 108.00 MHz
03 ch	AM 630 kHz	AM 630 kHz	AM 630 kHz
04 ch	AM 990 kHz	AM 990 kHz	AM 990 kHz
05 ch	AM 1440 kHz	AM 1440 kHz	AM 1440 kHz
06 ch	AM 1610 kHz	AM 1610 kHz	AM 1602 kHz
07 ch	AM 1700 kHz	FM 87.50 MHz	FM 87.50 MHz
08 ch	FM 87.50 MHz	FM 87.50 MHz	FM 87.50 MHz
09 ch	FM 87.50 MHz	FM 87.50 MHz	FM 87.50 MHz
10 ch	FM 89.10 MHz	FM 89.10 MHz	FM 89.10 MHz
11 ch	FM 87.50 MHz	FM 87.50 MHz	FM 87.50 MHz
12 ch	FM 90.00 MHz	FM 90.00 MHz	FM 90.00 MHz
13 ch	FM 106.00 MHz	FM 106.00 MHz	FM 106.00 MHz
14 ch	AM 530 kHz	AM 530 kHz	AM 531 kHz
15 ch	FM 87.50 MHz	FM 87.50 MHz	FM 87.50 MHz
16 ch	FM 87.50 MHz	FM 87.50 MHz	FM 87.50 MHz
17 ch	FM 87.50 MHz	FM 87.50 MHz	FM 87.50 MHz
18 ch	FM 87.50 MHz	FM 87.50 MHz	FM 87.50 MHz
19 ch	FM 87.50 MHz	FM 87.50 MHz	FM 87.50 MHz
20 ch	FM 87.50 MHz	FM 87.50 MHz	FM 87.50 MHz

The initial setting is performed in a following event:

- 1. When backup memory data is destroyed when reset is applied to the microprocessor.
- 2. When the power cord is plugged in to the AC wall outlet while pressing the POWER key.

4. TEST MODE

Setting method

Plug the power cord in the AC electrical outlet while depressing the "TUNING DOWN" key.

Cancellation method

Unplug the power cord from the AC electrical outlet.

Contents

1) Starting the main unit test mode

When plug the power cord in the outlet while depressing the "TUNING DOWN" key, the test mode is entered which uses the main unit keys. At this time the following three actions occur:


- The power comes ON automatically.
- The fluorescent display and all LEDs illuminate.
- All conditions except POWER ON/OFF are initialized.
 The all-illuminated state is cleared by pressing any main
 unit key. Also, any conditions changed during test mode
 are reinitialized when the test mode is cleared (by turning the AC power supply OFF).
- ② Automatic motor VR UP/DOWN (AMP)

 Operating the "TAPE 2" key actuates the motor VR as follows: 16 seconds UP → 16 seconds DOWN → STOP. Accordingly, "TAPE 2 MONITOR" switching cannot be done during the main unit test mode.
- ③ Mute signal output (AMP)
 No Selector MUTE (MUTE 1) control regulation is done whatsever.
- (4) 0~9, +10 testmode (TUNER)
- a) When the +10 key is not operated, channels 1 through 9 (1 ~ 9 keys) and channel 10 (0 key) can be called.
- b) When the +10 key is operated once, channels 11 through 19 (1 \sim 9 keys) and channel 20 (0 key) can be called.
- c) When the + 10 key is operated once more, the condition returns to that of a) above: "when the + 10 key is not operated."

- 5 Operations that can only be done by remote control
- a) AMP system: NONE
- b) TUNER system: NONE
- c) SURROUND system
- "P. CH CALL" key: Same operation as the "CENTER MODE" key.
- "DIRECT" key: Same operation as "TEST TONE" key.
- Naturally enugh, "P. CH CALL" "DIRECT" operation cannot be carried out.
- © During the test mode, because there is no 4/8 switching input status display, the fluorescent "SPEAKERS" display is substituted instead.
 (4/8 = Light on/Light off) As a result, please be careful concerning illumination of "SPEAKERS" during the test mode.
- ⑦ Cancellating the main unit test mode
 When the power cord unplug in the AC outlet during the main unit test mode, the test mode is cancelled and the initial condition restored.

5.Microprocessor: μPD78043GF/μPD78044GF (X14: IC1)

1 Microprocessor periphery block diagram




*1: KR-V6060 only

*3: KR-V8060 only

^{*2:} Usually, DSP LOGIC(LED), MUTING(LED) when KR-V5560.

^{*4:} Unused for KR-V5560.

② Port layout μPD78043GF [K,P,M,X,Y type] μPD78044GF [E.T type]



3 Pin description

For pin numbers marked by an asterisk(*) the upper row is μ PD78043GF and the lower () row is μ PD78044GF.

Pin No.	μ-Com No.	Port I/O	Name	Description				
1		OUT	GRID 6	FL Grid 6				
2		OUT	GRID 7	FL Grid 7				
3		OUT	GRID 8	FL Grid 8				
4		OUT	GRID 9	FL Grid 9				
5		OUT	GRID 10	FL Grid 10				
6		OUT	GRID 11	FL Grid 11				
7		OUT	GRID 1	FL Grid 1				
8		-	Vdd	Microprocessor power supply				
9		OUT	CLOCK (COMMON)	Clock for control IC (ANALOG SW	//PLL IC/DSP)			
10		OUT	DATA (COMMON)	Data for control IC (ANALOG SW	/PLL IC/DSP)			
11		OUT	DSP/DELAY ST.	DSP IC Strobe for control (LA278	5/LV1010)			
12		OUT	SELECTOR ST.	Strobe for control selector IC				
13		OUT	POWER RELAY	Power relay control	H: POWER ON	L: POWER OFF		
14		OUT	SPEAKER B RELAY	Speaker B relay control	H: SP B ON	L: SP B OFF		
15		OUT	SPEAKER A RELAY	Speaker A relay control	H: SP A ON	L: SP A OFF		
16		OUT	SPEAKER S RELAY	Surround speaker relay control	H: SP S ON	L: SP S OFF		
17		IN	RESET	Microprocessor reset				
18		OUT	4/8 CHANGEOVER RELAY	TAP control (KR-V6060 only)	H: HIGF TAP	L: LOW TAP		
19		OUT	VIDEO 1/2 SELECTOR	VIDEO Selector	H: VIDEO 2	L: VIDEO 1		
20		-	AVss	A/D power supply(GND)				
21		IN.	CE	Microprocessor CE				
22		OUT	TUNER MUTE	TUNER MUTE control	H: MUTE OFF	L: MUTE ON		
23		IN	STEREO	Stereo signal detection	H: MONORAL	L: STEREO		
24		IN	SIGNAL DETECT	Synchronized signal detection	H: NO TUNED	L: TUNED		
25		IN	IF COUNT(PLL)	IF COUNT Data (PLL DO)				
26		OUT	CE(PLL)	PLL CE				
*27	μPD78043GF	OUT	YM7128(DATA)	DSP IC Data for control				
*27	μPD78044GF	OUT	ATT(RDS)	Atineter control				
*28	μPD78043GF	OUT	YM7128(CLK)	DSP IC Clock for control				
*28	μPD78044GF	OUT	SIGNAL LEVEL(RDS)	SIGNAL LEVEL (A/D)				
29		-	AVdd	A/D Power supply				
30		-	AVref	A/D Reference voltage (+5V)				
31		IN	PROTECT	Protection detection	H: PROTECTION	L: NORMAL		
32		-	OPEN					
33		-	Vss	Microprocessor power supply(GN	ID)			
34		IN	X1	4.19 MHz Oscillator				
35		OUT	X2	4.19 MHz Oscillator				
36		IN	ENC_B	Encoder input B				
37		IN	ENC_A	Encoder input A				
38		OUT	VOLUME LED	VOLUME LED control	H: LED OFF	L: LED ON		
39		OUT	VOLUME UP	MOTOR VOLUME control (UP)				
40		OUT	VOLUME DOWN	MOTOR VOLUME control (DOW	N)			
41		1/0	S.DATA	8 bit system DATA				

For pin numbers marked by an asterisk(*) the upper row is μPD78043GF and the lower () row is μPD78044GF.

Pin No.	μ-Com No.	ription				
42		1/0	S.BUSY	8 bit system BUSY		
*43	μPD78043GF	OUT	YM7128(ST.)	DSP IC Strobe for control		
*43	μPD78044GF	OUT	RES(RDS)	RDS Reset		
*44	μPD78043GF	OUT	4053 P/D L	TC4053 Control pin		
*44	µРD78044GF	OUT	CLK(RDS)	RDS Clock		
*45	μPD78043GF	OUT	4053 INH	TC4053 Control pin		
*45	μPD78044GF	OUT	DATA(RDS)	RDS Data		
*46	μPD78043GF	OUT	DSP(LED)	DSP LED Control	H: LED ON	L: LED OFF
*46	μPD78044GF	OUT	START(RDS)	RDS Start		
47		IN	REMOCON	Remote control input		
48		-	GND			
49		OUT	STAND-BY(LED)	STAND-BY LED Control	H: LED OFF	L:LED ON
50		OUT	DSP LOGIC(LED)	DSP LOGIC LED Control	H: LED OFF	L: LED ON
51		OUT	D MUTE	DATA MUTE		· · · · · · · · · · · · · · · · · · ·
52		-	Vdd	Microprocessor power supply	-	
53		OUT	MUTE	Selector MUTE control	H: MUTE OFF	L: MUTE ON
54		IN	4/8 SELECTOR IN	Speaker inpedance changeover	Η: 4Ω	L: 8Ω
55		IN	KEY RETURN 4	Key return 4		
56		IN	KEY RETURN 3	Key return 3		
57		IN	KEY RETURN 2	Key return 2	33 10-1	
58		IN	KEY RETURN 1	key return 1		
59		IN	KEY RETURN 0	Key return 0		
60		OUT	SEGMENT 16	FL Segment 16/key scan 8		
61		OUT	SEGMENT 15	FL Segment 15/key scan 7		
62		OUT	SEGMENT 14	FL Segment 14/key scan 6		
63		OUT	SEGMENT 13	FL Segment 13/key scan 5		
64		OUT	SEGMENT 12	FL Segment 12/key scan 4		
65		OUT	SEGMENT 11	FL Segment 11/key scan 3		
66		OUT	SEGMENT 10	FL Segment 10/key scan 2		
67		OUT	SEGMENT 9	FL Segment 9/key scan 1		
68		OUT	SEGMENT 8	FL Segment 8/key scan 0		
69		OUT	SEGMENT 1	FL Segment 1		
70		OUT	SEGMENT 2	FL Segment 2		
71		-	Vload	FL Driver power supply(- 30V)		
72		OUT	SEGMENT 3	FL Segment 3		
73		OUT	SEGMENT 4	FL Segment 4		
74		OUT	SEGMENT 5	FL Segment 5		
75		OUT	SEGMENT 6	FL Segment 6		
76		OUT	SEGMENT 7	FL Segment 7		
77		OUT	GRID 2	FL Grid 2		
78		OUT	GRID 3	FL Grid 3		
79		OUT	GRID 4	FL Grid 4		
80		OUT	GRID 5	FL Grid 5		

KR-694/V5560/V6060

ADJUSTMENT

[FM,AM SECTION: E,T Type ONLY]


No.	ITEM	INPUT SETTINGS	OUTPUT SETTINGS	TUNER SETTINGS	ALIGNMENT POINT	ALIGN FOR	FIG.
FM S	ECTION	SELECTOR : FM			•		·
1	DISCRIMINATOR	(A) 98.0MHz	Connect a DC voltmeter between	AUTO or MONO	L3 (X05-)	0V	(a)
		1kHz,±75kHz dev 60dBμ(ANT input)	TP3 and TP4.	98.0MHz	L4 (X05-)	Minimum distortion	
2	DISTORTION (STEREO)	(C) 98.0MHz 1kHz,±68.25kHz dev Selector: L or R Pilot : ±6.75kHz dev 60dBμ(ANT input)	(B)	98.0MHz	IFT (W02-)	Mimum distortion. (L or R)	
3	SEPARATION	(C) 98.0MHz Stereo signal 60dBµ(ANT input)	(B)	AUTO 98.0MHz	VR3 (X05-)	Minimum crosstalk	
4	TUNING LEVEL	(A) 98.0MHz 0dev 14dBμ(ANT input)75Ω 18dBμ(ANT input)30Ω	(B)	AUTO or MONO 98.0MHz	VR1 (X05-)	Adjust VR1 and stop at the point where ED1(TUNED) goes on.	
AM	SECTION	SELECTOR : AM			·		
(1)	TUNING LEVEL	(D) 1008kHz 20dBμ(ANT input)	(B)	1008kHz	VR2 (X05-)	Adjust VR2 and stop at the point where ED1(TUNED) goes on.	

[COMMON]


No.	ITEM	INPUT SETTINGS	OUTPUT SETTINGS	AMPLIFIER	ALIGNMENT POINT	ALIGN FOR	FIG.
AUD	IO SECTION	SETTINGS	SETTINGS	SETTINGS	POINT		
<1>	IDLE CURRENT	-	(E) Connect a DC voltmeter across CP1(L) CP2(R) CP3(CENTER) CP4(REAR)	Volume:0	VR1(L) VR2(R) VR3(CENTER) VR4(REAR) (X07-)	22mV	(b)
POW	/ER:ON S	ELECTOR : CD(NO SIGNAI	L) SURROUNI	: PRO LOGIC			
<2>	PRO LOGIC S-OUT NOISE LEVEL	Short between TP6 and TP7 (B/5), between TP10 and TP11 (E/5). (X09-)	Connect a oscilloscope at Rear sp L or R. (Connect load with Rear sp L or R.)	Volume:MAX REAR LEVEL:MAX	VR3 (X09-)(E/5)	Minimum noise level (fig. © point of (c).	(c)

KR-694/V5560/V6060 ADJUSTMENT

(a)




(b) System connections/Reccordements du système/System-Anschlusse





KR-694/V5560/V6060 ADJUSTMENT

(c)





KR-694/V5560/V6060 KR-694/V5560/V6060 WIRING DIAGRAM







G










RDS UNIT KR-V 6060 E.T TYPE ONLY











FRONT






variations between individual instruments or/and

Les tensions c.c. doivent être mesurées avec un voltmètre à haute impédance. Les valeurs peuvent différer légèrement du fait des variations inhérentes aux appareils et aux instruments de mesure individuels.


mit einem hochohmigen Spannungsmesser ge-messen. Dabei schwanken die Meßwerte aufgrund von Unterschieden zwischen einzelnen Instrumenten oder Geräten u. U.geringfügig.

CAUTION: For continued safety, replace safety critical components only with manufacturer's recommended parts (refer to parts list) Δ Indicates safety critical components. To reduce the risk of electric shock, leakage-current or resistance measurements shall be carried out (exposed parts are acceptably insulated from the supply circuit) before the appliance is returned to the customer.

KR-694/V5560/V6060 Y05-2840-10 **KENWOOD**



2SD2012



TA8409S

TDA7330B

LA2785


NJM4580D-D

M5223P

NJM4580D-D

TDA7330B

TA8409S



LA2785





LA1851N

LA1831-KEN





NJM4565L





S-80740AL

DC voltages are as measured with a high impedance voltmeter. Values may vary slightly due to variations between individual instruments or/and

Les tensions c.c. doivent être mesurées avec un voltmètre à haute impédance. Les valeurs peuvent différer légèrement du fait des variations inhérentes aux appareils et aux instruments de mesure individuels.

Die angegebenen Gleichspannungswerte wurden mit einem hochohmigen Spannungsmesser gemessen. Dabei schwanken die Meßwerte aufgrund von Unterschieden zwischen einzelnen Instrumenten oder Geräten u. U.geringfügig.

CAUTION: For continued safety, replace safety critical components only with manufacturer's recommended parts (refer to parts list) 🛆 Indicates safety critical components. To reduce the risk of electric shock, leakage-current or resistance measurements shall be carried out (exposed parts are acceptably insulated from the supply circuit) before the appliance is returned to the customer.


Y05-2840-10


NJU7311L

NJU7313L

2/4 KR-694/V5560/V6060







DC voltages are as measured with a high impedance voltmeter. Values may vary slightly due to variations between individual instruments or/and


Les tensions c.c. doivent être mesurées avec un voltmètre à haute impédance. Les valeurs peuvent différer légèrement du fait des variations inhérentes aux appareils et aux instruments de mesure individuels.


Die angegebenen Gleichspannungswerte wurden mit einem hochohmigen Spannungsmesser gemessen. Dabei schwanken die Meßwerte aufgrund von Unterschieden zwischen einzelnen Instrumenten oder Geräten u. U.geringfügig. CAUTION: For continued safety, replace safety critical components only with manufacturer's recommended parts (refer to parts list) \(\Delta\) Indicates safety critical components. To reduce the risk of electric shock, leakage-current or resistance measurements shall be carried out (exposed parts are acceptably insulated from the supply circuit) before the appliance is returned to the customer.


3/4 KR-694/V5560

Y05-2840-10 KENWOO

BK







DC voltages are as measured with a high impedance voltmeter. Values may vary slightly due to variations between individual instruments or/and units

Les tensions c.c. doivent être mesurées avec un voltmètre à haute impédance. Les valeurs peuvent différer légèrement du fait des variations inhérentes aux appareils et aux instruments de mesure individuels.


Die angegebenen Gleichspannungswerte wurden mit einem hochohmigen Spannungsmesser gemessen. Dabei schwanken die Meßwerte aufgrund von Unterschieden zwischen einzelnen Instrumenten oder Geräten u. U.geringfügig.

CAUTION: For continued safety, replace safety critical components only with manufacturer's recommended parts (refer to parts list) \(\Delta\) Indicates safety critical components. To reduce the risk of electric shock, leakage-current or resistance measurements shall be carried out (exposed parts are acceptably insulated from the supply circuit) before the appliance is returned to the customer.

KENWOOD

---- -- -B LINE

KR-694/V5560/V6060 KR-694/V5560/V6060 EXPLODED VIEW (UNIT)



UNIT LIST

KR-694

DESTINATION		TUNER UNIT	MAIN AMP UNIT	AUDIO UNIT	DISPLAY UNIT
	K	X05-4460-11	X07-2770-11	X09-3940-11	X14-3880-11
Sigapore made	Р	X05-4460-11	X07-2771-02	X09-3940-11	X14-3880-11
•	M	X05-4460-21	X07-2780-22	X09-3940-11	X14-3880-22
	K	X05-4460-11	X07-2770-11	X09-3940-11	X14-3880-11
Malaysia made	P	X05-4460-11	X07-2771-02	X09-3940-11	X14-3880-11

KR-V5560

DESTINATION		TUNER UNIT	MAIN AMP UNIT	AUDIO UNIT	DISPLAY UNIT
	K	X05-4460-11	X07-2770-11	X09-3940-11	X14-3880-11
	Р	X05-4460-11	X07-2771-02	X09-3940-11	X14-3880-11
Sigapore made	Y	X05-4460-21	X07-2782-92	X09-3940-11	X14-3880-22
orgapore made	M	X05-4460-21	X07-2780-22	X09-3940-11	X14-3880-22
	X	X05-4460-71	X07-2780-11	X09-3940-11	X14-3880-71
	R	X05-4460-11	X07-2770-11	X09-3940-11	X14-3880-11
	К	X05-4460-11	X07-2770-11	X09-3940-11	X14-3880-11
Malaysia made	Р	X05-4460-11	X07-2771-02	X09-3940-11	X14-3880-11
	R	X05-4460-11	X07-2770-11	X09-3940-11	X14-3880-11

KR-V6060

DESTINATION		TUNER UNIT	MAIN AMP UNIT	AUDIO UNIT	DISPLAY UNIT
	К	X05-4460-11	X07-2770-10	X09-3940-10	X14-3880-10
	Р	X05-4460-11	X07-2771-01	X09-3940-10	X14-3880-10
Sigapore made	R	X05-4460-11	X07-2770-10	X09-3940-10	X14-3880-10
	Y	X05-4460-21	X07-2782-91	X09-3940-10	X14-3880-21
	М	X05-4460-21	X07-2780-21	X09-3940-10	X14-3880-21
	T	X05-4472-72	X07-2780-51	X09-3942-71	X14-3882-71
	E	X05-4472-72	X07-2782-70	X09-3942-71	X14-3882-71
	К	X05-4460-11	X07-2770-10	X09-3940-10	X14-3880-10
Malaysia made	Р	X05-4460-11	X07-2771-01	X09-3940-10	X14-3880-10
	R	X05-4460-11	X07-2770-10	X09-3940-10	X14-3880-10

Destin Re- nation Barks 在 可 音樂
R0502)
20111010
-694
* A
*
e4 22
•
l
重
*

(4) 1 日	H50 - 0.925 - 0.4 H50 - 0.925 - 0.4 H50 - 0.925 - 0.4 J50 - 0.925 - 0.4 J10 - 3.826 - 1.5 J19 - 3.826 - 0.5 J10 - 0.881 - 0.2 K29 - 5.837 - 0.3 K29 - 5.837	CARTON CASE CARTON CASE CARTON CASE CARTON CASE HOLDER HOLDER HOLDER HOLDER HOLDER CORD BUSHING (SURROUND) (CORD BUSHING BAND (CORD BUSHING BAND (SURROUND) (SURROUND	7 X X X X X X X X X X X X X X X X X X X	a a a a a a a a a a a a a a a a a a a
6440 6440	-0.0925-0 -0.0926-0 -9.3326-1 -9.3326-1 -9.355-0 -9.355-0 -9.355-0 -9.355-0 -9.355-0 -9.5534-0 -5.5534-0 -5.5534-0 -5.5537-0 -5.5537-0 -5.5637-0 -5.5637-0 -5.5637-0 -5.5637-0 -5.5637-0 -5.5637-0 -5.5637-0 -5.5637-0 -5.5637-0 -5.5637-0 -5.5637-0 -5.5637-0 -5.5637-0 -5.5637-0 -5.5637-0 -5.5637-0 -5.5637-0 -5.5637-0 -5.565-0 -5.	CARTON CASE CARTON CASE HOLDER	α ××× × γ α × × × × × × × × × × × × × ×	ν.Σ
6640 6641 6641 6642 6642 6642 6642 6643 6643 6643 6643 6653	7-0366-1 -3208-6 -3208-6 -3657-0 -2663-6 -2663	HOLDER R R R COMP BUSHING RANS, TREBLE) (SURROUND) (SURROU	σ.×≻π. × × × × × × × × × × × × × × × × × × ×	
6652 110	-0083-0 -5843-0 -5834-1 -5837-0 -5837-0 -5860-0 -5860-0 -5860-0 -5860-0 -00850-0 -00	RAND (SURROUND) (SURROUND) (SUREY) (PASS, TREBLE (BASS, TREBLE (BASS, TREBLE (TANDIN SELEC (TRNVIT S	0 × × × × × × × × × × × × × × × × × × ×	
6534 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	-5844-1 -5834-1 -5833-0 -5833-0 -5833-1 -5866-0 -5866-	(SURROUND) (10KEY) (BASS) TREBLE (BALANCE) ASSY (VOLUME (INPUT SELEC TRANSFORMER	0.×>× >× × × × × × × × × × × × × × × × ×	
11 0000 AAA A A A A A A A A A A A A A A	9-5866-0 9-5866-0 7-0848-0 7-0850-0 7-0851-0 7-0852-0 9-2909-0 9-2909-0	ASSY (VOLUME (INPUT SELEC TRANSFORMER TRANSFORMER TRANSFORMER TRANSFORMER TRANSFORMER TRANSFORMER TRANSFORMER	0. X > X X X X X X X X X X X X X X X X X	
6660 6660 6660 6660 118 665 118 665 118 665 118 665 665 118 665 118 665 118 665 118 118 118 118 118 118 118 118 118 11	7-0848-0 7-0850-0 7-0851-0 7-0852-0 7-0852-0 8-0128-3 9-2909-0 9-0333-0	TRANSFORMER TRANSFORMER TRANSFORMER TRANSFORMER TRANSFORMER TRANSFORMER	0 × × × × × × × × × × × × × × × × × × ×	
655 665 118 118 128 128 138 138 138 138 138 138 138 138 138 13	8-0128-3 9-2909-0 9-0333-0 9-2907-0	ING POST (E	X XX	
65 00 00 00 00 00 00 00 00 00 00 00 00 00	2-2608-4	TAPPING SCREW (3X12) SEMS (TAPTITE SCREW)(3X14) BINDIG HEAD TAPTITE SCREW	r r	
665 665 18 18 18 18 18 18 18 18 18 18 18 18 18	N89-3008-45 N89-3008-46 N89-3018-46 N29-0265-15	BINDING HEAD TAPTITE SCREW BINDING HEAD TAPTITE SCREW BINDING HEAD TAPTITE SCREW PUSH RIVET		
01 1A **	T90-0175-05 T90-0195-05	1 TYPE ANTENNA LØØP ANTENNA		
01 02 3A * *	Ж	-V6060		
003 004 118 118	A01-3098-11 A60-0525-21 A70-0962-15 A70-0963-05 A09-0146-08	METALLIC CABINET PANEL REMOTE CONTROLLER ASSY(-R0702) BATTEY COVER	KPYMR	
615 615 3A A * *	B03-2871-13 B03-2886-13 R46-0092-33 B46-0094-03 R46-0095-03	DRESSING PLATE ORESSING PLATE WARRANTY CARD WARRANTY CARD WARRANTY CARD	KPYMR TE Y Y	
	B46-0121-33 B46-0197-00 B46-0310-03 B58-0513-04 B58-0964-03	WARRANTY CARD QUESTIONAIRE CARD WARRANTY CARD CAUTION CARD CAUTION CARD CULION CARD CUL	KR Y XYR	
4 H P	B58-0965-03 B58-0966-03 B58-0970-03 B60-1441-00 B60-1442-00	CAUTION CARD (P.T.X) CAUTION CARD (E.L.M) CAUTION CARD (R.TYPE) INSTRUCTION MANUAL (ENGLISH) INSTRUCTION MANUAL (ENGLISH)	P MTE R KPYMR TE	

P.Canada R:Mexico E.Europe G:Germany M:Other Areas

K:USA T:England X:Australia

L:Scandinavia Y:PX(Far East, Hawaii) Y:AAFES(Europe)

## # # # # # # # # # # # # # # # # # #	Addre	ss New	Parts No.	Description	Destin Re-
LO7-0852-05		* #=	報報	品名/規	
NOB-0128-35		*	07-0852-0	TRANSFORME	~
NB9-3008-45			-0128-3 -2909-0 -0333-0 -2907-0 -2608-4	APTITE SCREW APPING SCREW (3X12) EMS (TAPTITE SCREW)(3X12) INDIG HEAD TAPTITE SCRE	£χ σ
T90-0175-05			-3008-4 -3008-4 -3018-4 -0265-1	INDING HEAD TAPTITE SCR INDING HEAD TAPTITE SCR INDING HEAD TAPTITE SCR USH RIVET	
KR-V5560	മെട		75-0 95-0	TYPE NOP AN	
### ### ### ### #### #### ############	4400	* * *	-3098-11 -0526-21 -0964-05	-V5560 METALLIC CABINET PANEL REMOTE CONTROLLER ASSY RATTERY CANGE	
B46-0121-33 WARRANTY CARD B46-0197-00 B58-0513-04 CAUTION CARD B58-0964-03 CAUTION CARD B58-0965-03 CAUTION CARD B58-0966-03 CAUTION CARD B58-097-03 B60-1453-00 INSTRUCTION MANUAL (ENGLISH B60-1455-00 INSTRUCTION MANUAL (CHINESE B60-1455-00 INSTRUCTION MANUAL (CHINESE B60-1456-00 INSTRUCTION MANUAL (CHINESE B60-1456-00 INSTRUCTION MANUAL (CHINESE B60-1456-00 INSTRUCTION MANUAL (CHINESE B70-259-15 AC POWER CORD B70-259-05 AC POWER CORD B70-259-05 AC POWER CORD B70-259-05 B70-259	ı «	* *	2887-1 -0092-3 -0094-0 -0095-0	DRESSING PLATE WARRANTY CARD WARRANTY CARD WARRANTY CARD WARRANTY CARD	×~~×
B58-0966-03 CAUTION CARD B58-0966-03 CAUTION CARD B60-1453-00 INSTRUCTION MANUAL (FRENCE B60-1455-00 INSTRUCTION MANUAL (FRENCE B60-1455-00 INSTRUCTION MANUAL (FRENCE B60-1456-00 INSTRUCTION MANUAL (FRENCE B60-1456-00 INSTRUCTION MANUAL (FRENCE B60-1456-00 INSTRUCTION MANUAL (FRENCE B20-265-05 AC POWER CORD E30-265-05 AC POWER CORD E30-265-05 AC POWER CORD E30-265-05 AC POWER CORD E30-265-05 AC POWER CORD E30-1297-05 INSULATING SHEET (FRONT) F20-1392-04 INSULATING SHEET (FRONT) INSULATING SHEET (FRONT) INSULATING SHEET (FRONT) INSULATING SHEET (FRONT) INSULATING SHEET F20-1392-04 INSULATING SHEET F20-1392-04 INSULATING SHEET F30-1392-04 I		**	46-0121 46-0197 58-0513 58-0964 58-0965	CARD (PRESET220	P Y Y RYR
B60-1456-00 INSTRUCTION MANUAL (SPANIE) E03-0115-05 AC PLUG ADAPTER E30-2565-05 AC POWER CORD E30-2650-05 AC POWER CORD E30-2650-05 AC POWER CORD E30-2650-05 AC POWER CORD E30-2717-05 AC POWER CORD E20-1297-05 INSULATING SHEET (CENTER FOOL 1997-05 INSULATING SHEET (CENTER FOOL 1997-04 INSULATING SHEET (CENTER FOOL		****	58-0966- 58-0970- 60-1453- 60-1454- 60-1455-	ANUAL C ANUAL C ANUAL C	EX JE
Control Cont			60-1456-0	NSTRUCTION MANUAL (E E
E30-2717-05 AC POWER CORD F20-1297-05 INSULATING SHEET (FRONT) F20-1297-05 INSULATING SHEET (CENTER F20-1392-04 INSULATING	20000		03-0115 30-2592 30-2605 30-2650	PLUG POWER POWER POWER	ΣΕ>-Χ σ π
F20-1297-05	۵		30-2717-0	POWER	×
H10-5676-02 POLYSTYRENE FOAMED FIXTURE H10-5680-02 POLYSTYRENE FOAMED FIXTURE H10-5681-02 POLYSTYRENE FOAMED FIXTURE H11-0061-04 POLYSTYRENE FOAMED FIXTURE H11-0061-04 CARTÓN BOARD H13-0147-14 CARTÓN BOARD H25-023-04 PROTECTION BAC (235X350X0.0	8 8,2C 0		20-1297-0 20-1297-0 20-1392-0 20-1393-0	NSULATING SHEET (FRONT) NSULATING SHEET (CENTER NSULATING BOARD NSULATING SHEET	X W X
H13-0147-14 CARTON BOARD H25-0232-04 PROTECTION BAG (235X350X0.0 H25-0341-04 PROTECTION RAG		** #	10-5676-0 10-5677-0 10-5680-0 10-5681-0 11-0061-0	STYRENE FOAMED FIXTUR STYRENE FOAMED FIXTUR STYRENE FOAMED FIXTUR STYRENE FOAMED FIXTUR STYRENE FOAMED BOARD	KPY KPY KPY KP KP KA KA
0-0924-04 ITEM CARTON		* *	H13-0147-14 H25-0232-04 H25-0361-04 H50-0924-04	35X350X0.	KPYXR
		Y:AAFES(Europe)	X:Australia M:Other Areas	A indicates safety	critical components

 New Parts Parts without Parts No. are not supplied. Les articles non-mentionnes dans le Parts No. ne sont pas fournis. Telle ofine Parts No. wer den night, gelanfest.

POST (EARTH) YMTE SCREW (SCREW (ST.2) TAPTITE SCREW (MAIL) HEAD TAPTITE SCREW ST.4) HEAD TAPTITE SCREW SCREW SCREW (MAIL) SCREW SCREW	TAPTITE SCREW TAPTITE SCREW	R Except E.T	×e××	SOWV SOWV J YMX X X X X X X X X X X X X X X X X X X	50WV 50WV 35WV 35WV	^	2 2	>> >	>>>	£ >-	4:KR-694 5:KR-V5560
GERTH) (GARTH) (3X12) SCREW)(3X14 PTITE SCREW	APTITE SC APTITE SC APTITE SC	ļu.	×e××	50WV 50WV 3	A # 50 A	>	2 2	>> >	>>>		1
WST (EARTH CREW (3X12) CREW (3X12) TITE SCREW)(APTITE APTITE APTITE	Cep	L		$v_1v_2v_2v_3$	- X J J X	2 X X X X X X X X X X X X X X X X X X X	50% 3 50% 50%	354V 164V 504V K	A D L 16 ₩ V	age 4
	HEAD HEAD VET	ANTENNA TENNA ADAPTOR	0400~	4.70F 1.00F 2.20F 0.0160F 0.0240F	1.00F 3.30F 100F 0.0470F	47UF 0.010UF 27PF 22PF 470PF	47UF 0.022UF 1.0UF 0.010UF	1.00F 470F 22PF 1.00F	100E 470E 0.470E 0.0470E 100PE	680PF 100PF 47UF 6800PF 15PF	S:Singapore made W:Malaysia made
BINDING POST TAPTITE SCREW TAPPING SCREW SERS (TAPTITE BINDIC HEAD TA	BINDING H BINDING H BINDING H PUSH RIVE	T TYPE ANTENNA LOGO ANTENNA ANTENNA ADAPTOR O5-446X-XX): E	CHIP C CHIP C CHIP C CHIP C	ELECTRO ELECTRO ELECTRO MYLAR	ELECTRO ELECTRO ELECTRO CHIP C ELECTRO	CHIP C CHIP C CHIP C CHIP C CHIP C CHIP C	ELECTRO CHIP C ELECTRO CHIP C	ELECTRO ELECTRO CHIP C ELECTRO CHIP C	BLECTRO BLECTRO CHIP C CHIP C	CHIP C CHIP C ELECTRO MYLAR CHIP C	R:Mexico
1.07-0647-03 N08-0128-35 N09-0333-05 N09-2907-05 N09-2907-05 N82-2608-46	N89-3008-45 N89-3008-46 N89-3018-46 N29-0265-15	190-017 190-019 190-018	CK73FB1 CE04LW1 CK73FB1 CK73FB1 CK73FB1	CEOALWIH4R7M CEOALWIH010M CEOALWIH2R2M CQ92FM1H163J	CEO4LW1H010M CEO4LW1H3R3M CEO4LW1V100M CK73FB1E473K CEO4LW1V100M	CEOALW1A470M CK73FB1H103K CC73FCH1H270J CC73FCH1H220J CK73FB1H471K	CEO4LW1C470M CK73FB1H223K CEO4LW1H010M CK73FB1H103K C91-0769-05	CEO4LW1H010M CEO4LW1C470M CC73FSL1H220J CEO4LW1H010M CK73FB1H102K	CEO4LW1V100M CEO4LW1C470M CEO4LW1HR47M CK73FB1E473K CC73FSL1H101J	CK73FB1H661K CC73FSL1H101J CE04LW1C470M CJ92FM1H682J CC73FSL1H150J	I K:USA P:Canada R
•		-					·		,		
Ž		18 8] L:Scandinavia
ວ 0 0 ∢∢ໝ∪ລ	முடிகோ	665 666 667	C1 ,2 C4 C5 C6 C9	011 013 014 021 , 22 021 , 22	0223 0224 027 027	C31 C32 C33 C34 C35 -38	C39 C40 C41 C41 C62	051 052 057 065 065	C71 C72 C103-106 C107 C112	C114 C115,116 C121,122 C135,136 C182	1 L:Scandinavia
1	NUB-0128-35 NO9-05 NO9-0333-05 NUS-2907-05 NUS-2907-05	NUB-0128-35 NU9-0333-05 NU9-0333-05 NU9-2907-05 NB2-2608-46 NB9-3008-45 NB9-3008-46 NB9-3018-46 NB9-3018-46 NB9-3018-46	NOB-0128-35 B NO9-2990-05 T. NO9-2990-05 T. NO9-2907-05 S. NO9-2907-05 S. NO9-2907-05 S. NO9-2008-46 B NO9-3008-46 B NO9-3008-46 B NO9-3018-46 B NO9-2008-5 T. NO9-0175-05 T. NO-0175-05 T. NO-0175-05 T. NO-0185-05 T. NO-0185-	NUG-0126-35 H	NOB-0128-35 NO97-2999-05 The NO97-2999-05 NO97-2907-05 NO97-2907-05 NO97-2907-05 NO97-2907-05 NO97-2907-05 NO97-2907-05 NO97-2907-05 NO97-2907-05 NO97-2907-05 TUNER UNIT(XO5-05 TUNER UNIT(X	NUMBER N	NOB-0128-35 H	19	1.22 CECALWIALAY OF CECALWIALAY OF CECALWIALAY OF CECALWIALAY OF CECALWIALAY OF CECALWIALD OF CECALW	19	19

ш	Ref. No.	Addre	8.55	Š	Parts No.	Description		8
	李明寺	每	H	Paris	19 19 19 19	部品名/规格	nation (‡ p)	Barks 未 表
<u> </u>					B60-1443-00 B60-1444-00 B60-1445-00 B60-1446-00 B60-1593-00	INSTRUCTION MANUAL (FRENCH) INSTRUCTION MANUAL (CHINESE) INSTRUCTION MANUAL (GE, DU) INSTRUCTION MANUAL (SPANISH) INSTRUCTION MANUAL (SPANISH)	បាសពេស ជ	
	ı		•		860-1594-00	TION MANUAL	ш	
ଶ୍ୟଶ୍ୟ	620 621 621 621 621	80000		***	E03-0115-05 E30-2592-15 E30-2605-05 E30-2650-05 E30-2721-05	AC PLUG ADAPTER AC POWER CORD AC POWER CORD AC POWER CORD AC POWER CORD	A X Y RE	
	630 631 632 633 634	288 20 20 20 20 20 20 20 20 20 20 20 20 20		* *	F20-1258-04 F20-1284-05 F20-1297-05 F20-1392-04 F20-1393-04	INSULATING BOARD (FRONT) INSULATING BOARD (FRONT) INSULATING SHEET (CENTER, REAR) INSULATING BOARD INSULATING SHEET	TYMTE	
				* * * *	H10-5676-02 H10-5677-02 H10-5678-02 H10-5679-02 H10-5680-02	POLYSTYRENE FOAMED FIXTURE (L) POLYSTYRENE FOAMED FIXTURE (R) POLYSTYRENE FOAMED FIXTURE (L) POLYSTYRENE FOAMED FIXTURE (R)	KPYMER KPYMER T KPR	ທທທທ⊐≖
	, , , , ,	··		* * *	H10-5681-02 H11-0061-04 H13-0147-14 H13-0160-04 H25-0232-04	POLYSTYRENE FOAMED FIXTURE (R) POLYSTYRENE FOAMED BOARD CARTON BOARD CARTON BOARD PROTECTION BAG (235X350X0.03)	KPR KPYMER KPYMER	3
	1111			* *	H25-0361-04 H25-0651-04 H25-0666-04 H50-0921-04 H50-0922-04	PROTECTION BAG (0232 PRINTED) PROTECTION BAG (0232 PRINTED) PROTECTION BAG (0361 PRINTED) ITEM CARTON CASE ITEM CARTON CASE	KPYMER T KPYER M	w w
				* *	H50-0923-04 H50-0985-04	ITEM CARTON CASE	T. K.P.R.	ഗാട
	638 639 640 641	20029	20	*	J02-0366-15 J02-1040-05 J19-3208-05 J19-3326-15 J19-3657-04	FOOT FOOT UNIT HOLDER UNIT HOLDER UNIT HOLDER(USABLE 319-3609-04	KPYMR TE	
€	643 648	11B		*	J19-3645-05 J42-0083-05 J61-0307-05	AM LOOP ANT. STAND POWER CORD BUSHING WIRE BAND		
	99999 99999 88999 98999	32 A B B B B B B B B B B B B B B B B B B	3.A 3.A		K29-5833-02 K29-5834-13 K29-5836-02 K29-5837-02 K29-5838-04	KNOB (10KEY) KNOB (10KEY) KNOB (POWER,TUNING) KNOB (POWER,TUNING) KNOB (BASS,TREBLE)	TEKPYMR	
	656 657 658	3 A A A			K29-5839-14 K29-5859-04 K29-5866-04	KNOB (BARANCE) KNOB ASSY (VOLIUME) KNOB (INPUT SELECTOR)		
4666	099 660 660 660	2222		* * * *	1.07-0843-05 1.07-0844-35 1.07-0845-05 1.07-0846-05	POWER TRANSFORMER POWER TRANSFORMER POWER TRANSFORMER POWER TRANSFORMER	orn+≻ E	
_	L:Scandinavia Y:PX(Far East, Hawaii)	via East, Ha	iwaii)	K:USA T:England	K:USA P:Canada F:England E:Europe (R:Mexico S:Singapore made G:Germany W:Malaysia made	4:KR-694 5:KR-V5560	1 68

* New Parts
Parts without Parts No. are not supplied
Les articles non mentionnes dans le Parts No. ne sont pas fournis.
Telle onne Parts No. werden nicht geliefert.

CK73FB1H682K CK73FB1H103K CC73FSL1H330J CE04LW1V100M CE04LW1H010M
CE04LW1HR33M CE04LW1H010M CK73FB1H103K C91-0769-05 CK73FB1H223K
CK73FB1H6B2K CE04LW1V100M CE04LW1V100M CE04LW1V100M CK73FB1E473K
CE04LW1A470M CK73FB1H103K CC73FCH1H270J CC73FCH1H220J CK73FB1H471K
CEO4LWIC470M CQ92FM1H223J CEO4HWIH2R2M CK73FB1H103K CEO4LWIV100M
CE04LW1HOR1M C91-0769-05 CE04LW1H010M CE04LW1C470M CC73FCH1H220J
CK73FB1H472K CE04LW1H010M C91-0769-05 CE04LW1C470M CK73FB1E473K
CE04LW1C470M CE04LW1H0R1M CC73FSL1H330J CK73FB1H102K CC73FSL1H150J
E20-0321-05
-0921
L72-0536-05 L40-1091-17 L30-0496-05 L30-0497-05 L79-0125-05
L30-0467-05 L79-0790-05 L40-1091-17 L39-1309-05 L40-1091-17
L77-1122-05
K:USA P:Canada T:England E:Europe

Description B	## # # # # # # ## ## ## ## ## ## ## ##	Paris No. Pari	Ba
	## # # # # # # # # # # # # # # # # # #	### Parts No. ### ## ## ## ### ## ## ## ### ### ##	### Parts No. ### ### ### ### ### ### ############
	BE20-04 1510-09 1510-09 1510-09 1510-09 1510-1	B B B B B B B B B B	### ### ### ### #### #################

∢

Les articles non mentionnes dans le Parts No. ne sont pas fournis.

NOW POLICE CO.
Parts without Parts No. are not supplied.
Les articles non mentionnes dans le Parts No. ne sont pas fournis.
Telle ohne Parts No. werden nicht geliefert.

Re-	_	N 4 4 N 4	٥			<u>د</u>								48.4		94
Desti-	tt e							1.0174								4:KR-694 5:KR-V5560
		0.00 WV 0.00 WV 0.00 WV 0.00 WV 0.00 WV	A# 52	63WV 35WV 250VAC Z 25WV	7#3 7#0	∧#6 0₩0	354V 3 2 2 2		p 37)	A A)		,	SCREW	5W 5W 5W J 1/4W	3 2W J 1/4W J 1/4W	de e
Description	品名/規格	100F 100F 1330UF 330UF 6 330UF 6	10000F X 1000PF K 470F 1 0.010UF Z 0.010UF P	2200F 100F 6800PF 0.010UF 330UF	4.70F 3 0.0100F 2 1000F K 0.0100F Z	470PF K 470PP K 470P 1 4700F 6	100F 479F 0.0100F 220PF 0.0470F	AL BOARD AL BOARD (3P)	PHONE JACK (25	(125V 64 (250V 14	oc.	COMPENSATION COIL TRANSFORMER	MACHINE	0.22 0.22 0.22 51STØR 22	4.7 10 3.3K	S:Singapore made W:Malaysia made
_	紐	ELECTRO ELECTRO ELECTRO ELECTRO	BLECTRW CERAMIC BLECTRW CERAMIC CERAMIC	BLECTRO BLECTRO MF CERAMIC ELECTRO	ELECTRO ELECTRO CERANIC CERAMIC CERAMIC	CERAMIC CERAMIC ELECTRO ELECTRO	ELECTRO CERAMIC CERAMIC CERAMIC CERAMIC	AC OUTLET LOCK TERMINAL LOCK TERMINAL PHONE JACK	MINIATURE P	FUSE (UL)	FUSE CLIP FUSE CLIP WIRE CLAMPER	PHASE COMPE POWER TRANS	BINDING HEAD	RD RD RO MULTIPLE RES RD	FL-PROOF RS RD RD	R:Mexico W.
Parts No.	的品类与	4EV1J100M 4EV2A106M 4EV1J331M 4EV1J331M	CEO4LWIVIO2M CK45FBIHIO2K CEO4LWIC470M CK45FFIHIO3Z CK45FE2HIO3P	504LW1J221M 504LW1V100M 91-1488-05 645FF1H103Z	304LW1A470M 304LW1V4R7M 445FF14103Z 445FB1H102K	CK45/B1H471K CK45/B1H471K CEO4LW1A470M CEO4LW03471M CK45/FF1H103Z	CEGALWIVIDOM CCASESLINA70.1 CKASEFIHI032 CCASESLIH221J CKASEFIHA732	1-0117-05 1-0047-05 1-0046-05 1-0069-15	-0188-05	-6029-05 -1026-05	3-0075-05 3-0075-05 1-0098-05	-0085-05 -0864-05	-3008-46	1-0840-05 1-0840-05 1-0840-05 1-0888-05 4NB2E220J	4KB3D4R7J 4NB2E100J 4NB2E332J	P:Canada
New	¥5.	00000	00000 04044	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	002222 903223	92999	90220	E03 E70 E70 E11 E11	113	F05	217	1.39	N35	R 890 R 890 R 890 R 890	RS1 RD1	K:USA
Address N	台	7.														
Ref. No.	中 田 市 中	9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	037 039,40 041-45 046	050 051 059 060	C62 ,63 C65 C70 C71 -74	C84 C85 C90 C91 C92,93	C95 , 96 C99 , 100 C101-103 C104, 105 C106	113 113 116 116	18	F1 F6	CN5 ,6 CN11,12 J2	L1 -4	J	CO 4 4 4 4 8	R9 ,10 R11 ,12 R13 ,14	L'Scandinavia
_				€				€		44	-					_

Re-	報												•	404
Desti- nation	## @									· · · · · · · · · · · · · · · · · · ·				
			24 1/44 1/44 1/44								R type		2 6.3WV 35WV 2 71WV	> A B B B B B B B B B B B B B B B B B B
Description	を 類 程	(19KHZ)	220 100 47 100 100 (22K)	(10K) (4.7K) 0 ØHM 0 ØHM			R) SIZER)				-XXI: K.P.	OUF UF UF UF	0.010UF 2 220UF 6 4.7UF 3 0.010UF 2 6800UF 7	6800UF 6 6800UF 6 10UF 6
	础	ESØNATØR	-PROOF RS	IMMING POT. IMMING POT. IP R	ZENER DIØDE ZENER DIØDE ZENER DIØDE ZENER DIØDE DIØDE	DIODE ZENER DIODE ZENER DIODE DIODE DIODE	DIQDE NIQDE DIQDE IC(AM,FM TUNER) IC(PLL SYNTHESIZER)	COP AMP X2) COP AMP X2) ANSISTOR ANSISTOR	TRANSISTOR TRANSISTOR TRANSISTOR TRANSISTOR TRANSISTOR	TRANSISTOR TRANSISTOR TRANSISTOR	ONT-ENI	1001	CERAMIC ELECTRO ELECTRO CERAMIC ELECTRO	ELECTRO ELECTRO ELECTRO
	-	RE	TREET	CCTT	251 251 261 261 010	ZEI	11100	O O SE SE SE	REEEE	TRA	UNITOXO7	WE SEE	99999	<u> </u>
S No.	ng l	295-05	IKB3D221J INB2E101J INB2E470J INB2E101J -3686-05	-3685-05 -1619-05 -0670-05 -0679-05	1.1N(B2) 195(B2) 1.3N(B2) 165(B2) 04	3 (B) 3 (B)	. N	550 14(R, 0) 15(F, E) 12K	37K 12K 37K 12K 3(E,F)	037K 1412K 037K	AMP UP		CK45FF1H103Z CE04LW0J221M CE04LW1V4R7M CK45FF1H103Z C90-3536-05	538-05 538-05 ¥1J100M
a.	論	L78-03	RS14KE RD14NE RD14NE RD14NE RD14NE	R12-36 R12-16 R92-06 P92-0	HZS5. RD5. 11 HZS3. RD3. 36 HSS104	1SS133 HZS10N(RD10ES(HSS104 1SS133	15S268 MA110 MA110 LA1851N LC7218	NJM4565D M5223P 2SC2714(R, 2SC1845(F, 2SC2412K	2SA1037K 2SC2412K 2SA1037K 2SC2412K 2SC2412K 2SD863(E,	2SC24 2SC24 2SA10	MAIN	CC45FSL1H10 CK45FF1H103 CQ92FM1H104 CK45FF1H103 CQ92FM1H104	CK45FF CE04LN CE04LN CK45FF C90-35	C90-39 C90-39 CE04LV
Par Is	*											<u> </u>		* *
d.	현 블													
ž	韓		,128	-103		112	,118	4	60	,110			118	4 K
	*	X	R31 R42 R111 R127 VR1	VR2 VR3 W100 W200	00000 60448	05 011 011 0111 0111	D117 D121 D125 D125 IC1 IC2	1C3 1C4 01 03	95 99 911 911	9102 9109 9111	DII	28882 28882	C17 C21 C22 C31 C33	C333

Re- marks								94	220	20000	• • • · · · · · · · · · · · · · · · · ·	94
Destination (任 向												4:KR-694
Description 鹳品名/獎格	0100E 0100E 0100E 2ENER 0100E 2ENER 0100E	0100E 0100E 0100E 0100E 0100E	10DE ENEK D10DE ENEK D10DE ENEK D10DE ENEK D10DE	1006 1006 EENER 01006 EENER 01006	DIODE TRANSISTOR TRANSISTOR TRANSISTOR	TRANSISTOR TRANSISTOR TRANSISTOR TRANSISTOR	TRANSISTOR TRANSISTOR TRANSISTOR TRANSISTOR TRANSISTOR	TRANSISTOR TRANSISTOR TRANSISTOR TRANSISTOR TRANSISTOR	TRANSISTOR TRANSISTOR TRANSISTOR TRANSISTOR	RANSISTOR RANSISTOR RANSISTOR RANSISTOR RANSISTOR	TRANSISTOR TRANSISTOR TRANSISTOR TRANSISTOR TRANSISTOR	S:Singapore made
	01 01 26 26 26	1000	22E	228		^						- B:Mexico
arts No. 品 書 号	-100 N(B2) S(B2)	∢	31 3N(B2) 3ES(B2) 5.1N(B2) 1ES(B2)	N(B2) SS(B2)	13 2790 145(F,E) 12(F,E) 534A(R,S)	12 51 74 10S(Q, R 85(F, E)	2SA1175(F,E) 2SA933S(Q,R) 2SC1740S(G,R) 2SC2765(F,E) 2SA1175(F,E)	2569335(Q,R) 25627465(P,E) 2562765(F,E) 25627465(P,E) 2562785(F,E)	1940A(R,S) 2003(L,K) 175(E,E) 333S(Q,R) 1740S(Q,R)	2785(F,E) 1175(F,E) 9335(Q,R) 17405(Q,R) 2785(F,E)	945(F,E) 92(F,E) 75(F,E) 335(Q,R) 7405(Q,R)	- 6000
e H	155131 55688B 15R139-1 HZS6.2N(RD6.2ES(HSS104 1SS133 HSS104 1SS133 HSS1044	15S131 HZS13N RD13ES HZS5.1 RD5.1E	HSS104 1SS133 HZS5.1N(B RD5.1ES(B HSS104	15513 NJM227 25C18 25A992 25A15	2SD2012 2SD2061 2SD2374 2SC1746 2SC2785	2SA11 2SA93 2SC17 2SC27 2SC27 2SC27	25C277 25C277 25C277 25C277 25C277	78039 28020 28411 28493 28017	2SC27 2SA11 2SA93 2SC17 2SC27	25C184 25A992 25A117 25A93 25C174	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
New Parts												
Address 位 富												
· 本	. 29 -33 -33	-40 -40 -44	4255 455 455 455 455 455 455 455 455 455	59 59 61 63	- 6 3	10001		-23			, 36 , 38	
Ref.	028 030 034 034	035 037 037 041	041 045 045 053 053	058 058 060 060 062	D62 IC1 Q1 Q7 Q8	66665	912 913 913 914	Q14 Q21 Q21 Q24 Q24	025 025 031 031	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	033 033 039 040	
	444					ବବବ			€			

品 22
-PROOF RS 4.7 10 3.3K -PROOF RS 560
10 47 47 -PROVE RS 150 -PROVE RS 270
-PROOF RS 270 18 6.8K 47 RBON 3.3M
RD 1.5 FL-PROOF RS 390 TRIMMING POT. (2.2
MAGNETIC RELAY MAGNETIC RELAY MAGNETIC RELAY MAGNETIC RELAY
MAGNETIC RELAY MAGNETIC RELAY MAGNETIC RELAY SLIDE SWITCH
IQDE IQDE ENER DIQDE IENER DIQDE IQDE
900 900 900 900 900 900
ZENER DIØDE ZENER DIØDE ZENER DIØDE ZENER DIØDE ZENER DIØDE
ZENER DIØDE DIØDE DIØDE ZENER DIØDE ZENER DIØDE
WDE WDE WDE WDE
308 80E
R.Mexico S:Singapore made G:Germany

* New Parts

V 4

ŝ

PROOF

87888

R014NB2E220J RS14KB3D4R7J RD14NB2E100J PD14NB2E332J RD14NB2E332J

ις **4**

RS. RS.

-PROOF

8585

RD14NB2C112J RS14KB3A561J RD14NB2E100J RD14NB2E470J RS14KB3D151J

4 10 %

RES 1

RD RD RD MULTIPLE F RD

R90-0840-05 R90-0840-05 R90-0840-05 R90-0866-05 R014NB2E220J

ŝ

-PROOF

-58888 8888

RS14KB3D4R7J RD14NB2E100J RD14NB2E332J RD14NB2C112J RD14NB2C112J

4:KR-694 5:KR-V5560 6:KR-V6060

S.Singapore made W:Malaysia made

G:Germany **В**:Мехісо

E:Europe

Y:PX(Far East, Hawaii) f:AAFES(Europe) L:Scandinavia

critical components.

indicates safety

M:Other Areas

X:Australia T:England K:USA

indicates safety critical components

* New Parts Parts without Parts No. are not supplied Las articles onon mentionins dans le Parts No. ne sont pas fournis. Telle other Parts No. werchen nicht noulerfert
S out

No.13

Re-marks 會學

Desti- R nation m (# @) f

品名/類

Description

Parts No. 褲 αď

Address New Parts 位 首 新

No.12

Les articles non mentionnes dans le Parts No, ne sont pas fournis. Telle onne Parts No, werden nicht geliefert.

Parts without Parts No. are not supplied

10WV 6.3WV 2

10UF 47PF 0.010UF 220PF 0.047UF

ELECTRO CERAMIC CERAMIC CERAMIC CERAMIC

CC45FSL1H470J CC45FSL1H470J CK45FF1H103Z CC45FSL1H221J CK45FF1H473Z

BOARD

AC OUTLET LOCK TERMINAL B LOCK TERMINAL B

PHONE

E03-0117-05 E70-0047-05 E70-0046-05 E11-0127-05 E11-0127-05

 $\triangleleft \triangleleft$

PHONE JACK PHONG JACK MINIATURE PHONE J AC OUTLET AC OUTLET

E11-0190-05 E63-0069-15 E11-0188-05 E03-0108-05 E03-0109-05

470PF 470PF 47UF 470UF 0.010UF

CERAMIC CERAMIC ELECTRO ELECTRO CERAMIC

CK45FB1H471K CK45FB1H471K CE04LW1A470M CE04LW0J471M CK45FF1H103Z

E SE

T3.15AL) T3.15AL) T2.5AL) T1AL)

(SEMKØ) (SEMKØ) (SEMKØ) (SEMKØ)

FUSE FUSE FUSE FUSE

F05-3121-05 F05-3121-05 F05-2525-05 F06-1022-05

E E

CLIP CLIP CLIP CLIP CLIP

FUSE (FUSE (FUSE (WIRE (

J13-0075-05 J13-0075-05 J13-0075-05 J13-0075-05 J11-0098-05

EX.

COIL

PHASE COMPENSATION COMPENSENTER POWER TRANSFORMER POWER TRANSFORMER

L39-0085-05 L07-0865-05 L07-0866-05 L07-0866-05

BINDING HEAD MACHINE SCREW

N35-3008-46

	No. are not supplied	Les articles non mentionnes dans le Parts No, ne sont pas fournis.	wenden nicht geliefent.
* New Parts	Parts without Parts No. are not supplied	Les articles non mentionnes d	Telle ohne Parts No. wenden nicht geliefent.

No.14

ation marks 何會為							9 4 9	\$ \$ \$ \$ \$ \$ \$	0000		04004	4:KR-694 5:KR-V5560 6:KR-V6060
t nat												4.00
Description 数晶色/凝晶	100E 100E	0100E 0100E 0100E	10DE :0 1C) 3T0R	STER STER STER STER STER	STOR STOR STOR STOR STOR	STOR STOR STOR STOR STOR	STGR STGR STGR STGR STGR	STGR STGR STGR STGR STGR	STOR STOR STOR STOR STOR	STOR STOR STOR STOR	STOR STOR STOR STOR STOR	S:Singapore made W:Malaysia made
	DIODE DIODE DIODE ZENER D ZENER D	ZENER D ZENER O DIØDE DIØDE ZENER D	ZENER D DIODE DIODE ICCVIDE TRANSIS	TRANSIS TRANSIS TRANSIS TRANSIS	TRANSIS TRANSIS TRANSIS TRANSIS	TRANSIS TRANSIS TRANSIS TRANSIS	TRANSIS TRANSIS TRANSIS TRANSIS	TRANSIS TRANSIS TRANSIS TRANSIS	TRANSIS TRANSIS TRANSIS TRANSIS	TRANSIS TRANSIS TRANSIS TRANSIS	TRANSIS TRANSIS TRANSIS TRANSIS	R:Mexico G:Germany
Parts No.	3 14A V(B2) 5(B2)	., 1N(B2) 1ES(B2) 04 33 ., 1N(B2)	1ES(82) 04 33 2790 845(F,E)	2(F,E) 34A(R,S) 12 61 74	2SC1740S(Q,R) 2SC2785(E,E) 2SA1175(F,E) 2SA933S(Q,R) 2SC1740S(Q,R)	2SC2785(F,E) 2SA1175(F,E) 2SA933S(Q,R) 2SC1740S(Q,R) 2SC2785(F,E)	140S(Q,R) 185(F,E) 140A(R,S) 103(L,K) 75(F,E)	933S(Q,R) 1740S(Q,R) 2785(F,E) 11175(F,E) 933S(Q,R)	740S(Q,R) (85(F,E) (45(F,E) (2(F,E) 75(F,E)	33S(Q,R) 740S(Q,R) 765(F,E) 845(F,E) 92(F,E)	2222BT 255BT 255BT 470BT 493BT	P:Canada E:Europe
***	155133 HSS104A 155131 HZS13N(B2) RD13ES(B2)	HZS5. RD5.11 HSS10 1SS13 HZS5.	RD5.1 HSS10 1SS13 NJM22 2SC18	2SA15 2SA15 2SD20 2SD20 2SD20 2SD23	2SC17 2SC27 2SA11 2SA93 2SC17	2SC27 2SA11 2SA93 2SC17 2SC27	2SC17 2SC27 2SC39 2SC20 2SC20	2SA93 2SC17 2SC27 2SC27 2SA11 2SA93	2SC17405 2SC27850 2SC18450 2SA99206 2SA11750	250217 250217 250218 250318	2S022 2S022 2S022 2SB14 2SB14	K:USA T:England
dress New					<u> </u>		<u></u>					Hawaii)
ef. No. Addr	37 -40 41 -44 41 -44 45 -52 45 -52	053 -56 053 -56 058 59 060 61	60 ,61 62 ,63 62 ,63 C1 1 -6	1000	##88##	913 914 921 -23 921 -23	924 925 926 931	931 932 933 933	334 334 337 336 39	39 440 441 444 444	01,102 01,102 01,102 03,104	L:Scandinavia Y:PX(Far East, Hawaii)

marks			0 0 W 4	99 9		9.9			9.6			5560
nation (# (A)	ш			¥ >-								4:KR-694 5:KR-V5560
	1/4W 2W 2W 2W 1/4W	1/4W 1/4W 1/4W 1/4W										
#	20000	2222										nade
A A A	100 270 270 270 18	6.8K 47 1.5 390 T.(2.2K)	RELAY RELAY RELAY RELAY RELAY	RELAY RELAY RELAY TCH				ш ш ш			fet sal	S:Singapore made W:Malaysia made
126	8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	RS POT		RE RE	100E 100E		DIODE DIODE DIODE DIODE DIODE	100			DI ØDE DI ØDE	isi ≥
	RD FL-PROOF FL-PROOF FL-PROOF RD	RD RD RD FL-PROOF TRIMMING	MAGNETIC MAGNETIC MAGNETIC MAGNETIC MAGNETIC	MAGNETIC MAGNETIC MAGNETIC SLIDE SWI SLIDE SWI	DIODE DIODE ZENER D ZENER D DIODE	DIØDE 0100E 0100E 0100E 0100E	ZENER D ZENER D ZENER D ZENER D ZENER D	ZENER D DIØDE DIØDE ZENER D ZENER D	0100E 0100E 0100E 0100E	01006 01006 01006 01006	ZENER D ZENER D DIØDE DIØDE DIØDE	R:Mexico G:Germany
ole Mar	4NB2E101J 4KB3D271J 4KB3D271J 4KB3D271J 4NB2E180J	E682J E470J E1R5J A391J	8-05 2-05 5-05 5-05	6-05 7-05 12-05 0-05	1(B2) 3(B2) 3(B2)	2LFA 2LFA 100	4(B2) 5(B2) 4(B2) 5(B2) 4(B2)	5(B2) -100 (B2) (B2)		A -100	2N(82) ES(82) 3	P:Canada F:Furone
	R014NB2 RS14KB3 RS14KB3 RS14KB3 RD14NB2	RD14NB2 RD14NB2 RD14NB2 RS14KB3 R12-161	S51-2078- S51-2092- S76-0005- S76-0005- S76-0005-	\$76-0016- \$76-0017- \$76-0009- \$31-2132- \$31-3010-	HSS104A 15S131 HZS5.1N(B2 RD5.1ES(B2 D5SBA20F03	RBV-602LFA DSSBA20F03 RBV-602LFA S568B 15R139-100	HZS6.2N RD6.2ES HZS8.2N RD8.2ES HZS2.7N	RD2.7ES(B2) S5688B 15R139-100 HZS16N(B2) RD16ES(B2)	HSS104 1SS133 HSS104 1SS133 HSS104	155133 HSS104A 155131 55688B 158139-	HZS6.2 RD6.2E HSS104 1SS133 HSS104	K:USA T:Fooland
A ME												۽ ا
Address to the total tot												L:Scandinavia
. *	96	.92	aaaa		ស្តេ	-12 -12		117	-23 -23	1229 1339 1339	-40	L: Scandinavia
# ¥ £.	R71 R76 R77 R78	R81 R91, R128 R170,	22222	**************************************	00 00 00 00 00 00 00	000000000000000000000000000000000000000	013 014 015	015 016 018 018	021 021 024 024 025	025 028 028 030 030	034 034 035 037	-

Les articles non mentionnes dans le Parts No. ne sont pas fournis.

Parts without Parts No. are not supplied.

4 4

* New Parts	Parts without Parts No. are not supplied	Les articles non mentionnes dans le Parts No. ne sont pas fournis.	Teile ofine Parts No. wenten night genefent.
*	g.	l.es	je

No.19

marks.	編		99								0 004		34
Destr- nation				1 T E		7.E		14. A.					4:KR-694 5:KR-V5560
	奉				онсмоня тсэ					R		164V 504V 5.54V 104V 354V	nade ade
Describtion	品名/規	ಷ್ಣಜ	ധയയമ	E E X2)	ICCANALWG SWITCH) ICCANALWG SWITCH) ICCONLBY PRO LOGIC DE DI BI-POLAR IC ICCOP AMP X2)	ICCMNTOR CONTROL) 1CCMP AMP X2) 1CCRDS DEMODULATOR) 1C 1C	ANSISTOR	~~~~	TRANSISTOR TRANSISTOR TRANSISTOR DIGITAL TRANSISTOR TRANSISTOR	or or or or 14-388X-XX	1 2 32	4.70F 10F 0.047F 100UF 4.70F	S:Singapore made W:Malaysia made
	器	6 8 DIWDE R DIWDE	E DIØDE R DIØDE R DIØDE R DIØDE	E R DIØDE R DIØDE P AMP X:	NALWG NALWG WLBY P II -PØLA	CCMNTNR CCONT AMPCOCRDS DEM	RANSISTOR IGITAL TRA RANSISTOR RANSISTOR RANSISTOR	RANSISTOR RANSISTOR RANSISTOR RANSISTOR	ASISTOR ASISTOR ASISTOR TAL TR ASISTOR		5,0	CTR®	
		DINDE DINDE ZENER ZENER DINDE	DIGDE ZENER ZENER ZENER ZENER ZENER	DIWDE DIWDE ZENER ZENER ICCOP	10.0A 10.0A 10.01 10.08	10.08 10.08 10.08	TRAN DIGI TRAN TRAN	TRAN TRAN TRAN	TRAN TRAN TRAN DIG	TRANSI TRANSI TRANSI		BACK BACK BLEC	R:Mexico
rts No.	幸 哈	04A 31 700(P2) 765(B2)	N(B2) S(B2) I(B2) S(B2)	8 (82) (82) (90 - 0	31. 11. 5 5 600-0	95 55L 508 3H-4600 1ES	2 2 2(P,E) 31(R,S)	2SA1123(R, S) 2SA992(F, E) 2SC2631(R, S) 2SA1123(R, S) 2SA933S(Q, R)	78(B) 40S(Q,R) 85(F,E) 4ES	2SC1740S(0, R) 2SC2785(F, E) 2SC3940A(R, S) 2SC2878(B) DISPLAY		1-3224-05 7-3253-05 7-1827-05 74LW1A101M	P:Canada
יי פיי	- E	HSS104A 1SS131 HZS4.7N 954.7ES	15S131 HZS5.1N(B2) BD5.1ES(B2) HZS10N(B2) RD10ES(B2)	HSS104 1SS133 HZSS.1N(B2) RDS.1ES(B2) NJM4S80D-D	X)P23131. NJP23111. LA2785 LV1010 NJM4580D-D	TA8409S NJM4565L TDA7330B LC6543H-46	UN4212 DTC124 UN4212 2SA992 2SC263	25A117 25A999 25C26 25A117 25A93	2SC2878(2SC1740S 2SC2785(DTC124ES	25027 25027 25039 25039	830-2 830-2 830-2 830-2 830-2	C90-3 C90-3 C90-1 CE04L CE04L	KUSA
S New	star.		-										- ,
Addres	海												L:Scandinavia
o Z	##	04 0		99-	æ	, 12 2 2 , 2	, 2 -14 -18	.20 -36 -40 ,42	-47	, 52	, 42	9,	L'Scandinavia
Ref.	数	039 039 041 041	042 051 051 052 052	D61 D61 D301 D301 IC1	103 103 104 105	IC9 IC11,12 IC201 IC202 Q1 ,2	91 94 94 911	019 033 037 041 043	Q44 Q48 Q48 Q49 Q49	951 951 953 954	041 043 046 048	000 000 000 000 000 000 000 000 000 00	

Re· marks									\$ 94	S				94
Destination		0 H H H	16 17 16 16 16		16 16	TE.			<u>⊢</u>					4:KR-694 5:KR-75560
		> > >	> >		, K) , K)		1/6% 1/4% 1/4% 1/4%	1/4W 1/4W 1/4W 1/4W 1/4W	176¥ 174¥ 29					
*	164V 2 2 8 8 8	35WV K 35WV Z 35WV	35WV 2 35WV 2		100H 100H 10H)	(ZHI	80000		2.2.2	^				made
scription * / #	100UF 0.010UF 0.047UF 330PF 4.7UF	47UF 270PF 19UF 0.010UF	27PF 10UF 0.010UF 47UF 0.010UF		INDUCTORC INDUCTORC INDUCTORC (BMHZ)	(4.00MHZ	39.0K 15 15 8.2 220	330 220 220 330	. 0K 0 30 100KX4 100KX4	100KX4 200K) 2.2K)				S:Singapore made
De B	1	BLECTR& MF BLECTR& CSRAMIC BLECTR&	CERAMIC BLECTR& CERAMIC BLECTR& CERAMIC	PHONG JACK PHONG JACK	SMALL FIXED INDUCTORK (10UH, R SMALL FIXED INDUCTOR(10UH, R SMALL FIXED INDUCTOR(10H) RESONATOR (6MHZ) CRYSTAL RESONATOR(4.332MHZ	RESONATOR	X X X X X X X X X X X X X X X X X X X	22222	RD RD FL-PROOF RS 3 POTENTIOMETER(POTENTIOMETER(POTENTIOMETER(TRIMMING POT.(DIODE DIODE ZENER DIODE ZENER DIODE DIODE	01008 01008 01006 01008 01008	0100E 0100E	R:Niexico S:
Parts No.	EWICIOIS PF1H1032 PF1H4733 P751 (05)	C90-3247-05 CF92EV1H271K CE04LW1V100M CKL5FF1H1032 CE04LW1V100M	CC45FCH1H270J CE04LW1V100M CK45FFH103Z CF04LW1V470M CK45FFH103Z	E63-0067-15 E63-0068-15	L40-1001-17 L40-1001-17 L40-1091-17 L78-0290-05 L77-2002-05	178-0503-05	RN14BK2C3902F RD14NB2E150J RD14NB2E150J RD14NB2E8R2J RD14NB2E8R2J	RD14NB2E331J KD14NB2E221J RD14NB2E221J RD14NB2E221J RD14NB2E331J	RD14NB2C102J RD14NB2E100J RS14KB3D331J R29-5087-05 R29-5068-05	R29-5088-05 R05-5060-05 R12-1617-05	HSS104 1SS133 HZSS.1N(B2) RDS.1ES(B2) HSS104	1SS133 HSS104A 1SS131 S5686B 1SR139-100	HSS104 1SS133	K:USA P:Canada
Paris	- <u></u>													
Address										W. E.				avia
ž s	227	,304	,307	7,	,202	01	,94 5,116	1,122 3,124 3,154 9,160	3 7,218 9		-10 -10	44499 44499	28	L'Scandinavia
	0205 0207 0208, 0210-	Critical teal teals to a	C306 C308 C309 C311 C312	3.1	L1 L201 L203 X1 X201	X202	R51 R54 R97 R93 R115	R12 R12 R15 R15 R15	R21 R30 VR1 VR1	VR1 VR2 VR3	03 03 011 011	021 023 023 025 025	027 027	

★ New Parts

Re-	agr KS 参]99
sti-	-6				TE	E	Ħ B		KPMXYR	35			4:KR-694 5:KR-V5560 6:KR-V6060
	格	35WV 10WV J 16WV	10WV K 2 16WV J	K J 358V 509V K	J Z 354V	J 354V K 104V K		508V 508V J 3 108V	10WV 0 100WV 3	C J 16WV 16WV 50WV		C J 164V 354V	ade de
Description	3 品名/規	100F 220UF 0.347UF 0.022UF 47UF	1000F 1000PF 0.022UF 47UF 0.10UF	1000PE 680PE 10UF 1.0UF 220PE	22PF 100PE 47PE 10UF 680PF	39PF 10UF 220PF 100UF 1000PF	0.012UF 3300PF 4.7UF 100PF 0.010UF	10F 1.00F 220PF 100PF 100UF	100UF 10PF 1.0UF 220PF 2.0PF	7.0PF 33PF 47UF 22UF 1.0UF	220PF 100PF 47UF 68PF 220PF	2.0PF 68PF 22UF 10UF 0.033UF	S:Singapore made W:Malaysia made
	器	ELECTRO ELECTRO MYLAR MYLAR ELECTRO	BLBCTRG CERAMIC CERAMIC ELECTRO MYLAR	CERAMIC ME ELECTRO ELECTRO CERAMIC	CERAMIC CERAMIC CERAMIC ELECTRO CERAMIC	CERAMIC ELECTRO CERAMIC ELECTRO CERAMIC	MYLAR MYLAR ELECTRO CERAMIC MYLAR	ELECTRO ELECTRO CERAMIC CERAMIC ELECTRO	ELECTRO CERAMIC BLECTRO CERAMIC CERAMIC	CERAMIC CERAMIC BLECTRO BLECTRO BLECTRO	CERAMIC CERAMIC ELECTRO CERAMIC CERAMIC	CERAMIC CERAMIC ELECTRO ELECTRO MYLAR	R:Mexico G:Germany
Parts No.	日 日 日	CEO4LW1V100M CEO4LW1A221M CO92EM1H473J CO92EM1H223J CEO4LW1C470M	CE04LW1A101M CK45FB1H102K CK45FF1H223Z CE04LW1C470M CG92FM1H104J	C91-0757-05 CF92FV1H681J CE04LW1V100M CE04LW1H010M C91-0749-05	C91-0729-05 C91-0745-05 C91-0737-05 CE04LW1V100M C91-0755-05	C91-0735-05 CED4LW1V100M C91-0749-05 CEO4LW1A101M C91-0757-05	C092FM1H123J C092FM1H332J CE04LW1V4R7M C91-0745-05 C093HP2A103J	C90-3253-05 CE04LW1H010M CC45FSL1H221J CC45FSL1H101J C90-3222-05	CC04LW1A101M CC45FSL1H100D CC04LW2A010M CC45FSL1H221J CC45FSL1H020C	CC45FSL1H070C CC45FSL2H330J CE04LH1C470M CE04LH1C220M CE04LH1C220M	CC45FSL1H221J CC45FSL1H101J CE04LW1A470M CC45FSL1H680J CC45FSL1H221J	CC45FSL1H020C CC45FSL2H680J CE04LW1C220M CE04LW1V100M CU92FM1H333J	L KCUSA P.C.mada I T.C.maland E.C.more '
S New													
Addres	4												 LiScandinavia YdYX(Far Elost, Mawaii)
Ref. No.	参照報记	C79 -82 C83 C84 C85 C86	C87 C89 C91 C92	C95 C96 C97,98 C99,100 C101,102	C103, 104 C105, 106 C107, 108 C109, 110	C121, 122 C123, 124 C125, 126 C127, 128 C129, 130	C131, 132 C133, 134 C135, 136 C137, 138 C139	C151 C152 C153,154 C155-158 C159	C160 C161,162 C163,164 C165,166 C167,168	C167, 168 C169, 170 C171, 172 C173 C173	C183, 184 C185-188 C189, 190 C191, 192 C193, 194	C195,196 C197,198 C200 C201,202 C203,204	L:Scandinavia

Re- marks (備考	S.]_
Destination (社 向			8 H H	E.									4:KR-694
**			ズスズスス	XXSXL JXSO¥ S¥	164V 164V J Z Z	164V K J J 104V	3 3 3 1040	354V 504V 354V 354V J	JOWV J 50WV 35WV	50WV 35WV J 50WV	50#V 35#V 50#V 35#V 35#V	50WV 50WV 10WV	ade
Description 都 品 名 / 規		394	220PF 220PF 220PF 220PF	220PF 220PF 1.0UF 220PF	22UF 47UF 100PF 4700PF 0.010UF	22UF 1000PF 0.010UF 2200PF 220UF	0.033UF 1500PF 0.033UF 1.0UF 220UF	100F 2.20F 100F 100F 0.820F	0.47UF 47UF 0.10UF 0.47UF 4.7UF	0.470F 4.70F 0.150F 3.30F 0.150F	3.3UF 0.15UF 4.7UF 0.47UF 4.7UF	0.470F 0.100F 1.00F 2200F	S:Singapore made
Ga	1 22222	- 1	CERAMIC CERAMIC CERAMIC CERAMIC CERAMIC	CERAMIC CERAMIC ELECTRO CERAMIC CERAMIC	ELECTRO ELECTRO CERAMIC CERAMIC CERAMIC	ELECTRO CERAMIC MYLAR MYLAR ELECTRO	MYLAR MYLAR MYLAR MF	BLECTRO BLECTRO BLECTRO BLECTRO	MF ELECTRO MYLAR ELECTRO ELECTRO	ELECTRO ELECTRO MF ELECTRO MP	BLECTRO MF ELECTRO ELECTRO ELECTRO	BLECTRO MYLAR BLECTRO BLECTRO	4.00000
Parts No. 略 報 身		AUDIO	C90749-05 C91-0749-05 C91-0749-05 C91-0749-05 C91-0749-05	C91-0749-05 C91-0749-05 CE04LW1H010M C91-0749-05 C91-0729-05	CEO4LW1C220M CEO4LW1C470M CC45FSL1H101J CK45FF1H472Z CK45FF1H103Z	CEOALWIC220M CK45FB.H102K CQ92FM.H103J CQ92FM.H222J CEO4LWIA22IM	CQ92FM1H333J CQ92FM1H152J CQ92FW1H333J CF92FV1H1O5J CEQ4LW1A221M	CEO4LW1V100M CEO4LW1V20M CEO4LW1V100M CEO4LW1V100M CF92FV1H824J	GF92FV1,4474 CEG4LW1A470M CG92FM1H104J CEG4LW1HR47M CEG4LW1V4R7M	CEO4LW1HR47M CEO4LW1V4R7M CF92FV1H154J CEO4LW1H3R3M CF92FV1H154J	CEO4LW1H3R3M CF92FV1H1S4J CEG4LW1V4R7M CEO4LW1HR47M CEO4LW1WR7M	CEO4LW1HR47M CO92FM1H104J CEO4LW1H010M CEO4LW1A221M	d sports Qui
Ne Parts]
Address 位 篇													
af. No. 無無。	13, 104 15, 106 17, 108 19, 110		44 66 110 120	116	3,24 5,26 7,28 9,31	333333333333333333333333333333333333333	#10.05	80 mms	93 . 59	2 E 4 S S S S S S S S S S S S S S S S S S	mm 0 - 21	3 ,75 6 ,77	- Company
Ref.	9103, 9105, 9107, 9109,	1	C3 C3 C11	C13 C15 C17 C19	2222	003	0.44 0.45 0.45 0.47	0.50	056 057 058 060 061	900	C68 C69 C70 C71 C72	C77 C77 C76	1

* New Parts Parts without Parts No. are not supplied.
Les articles non mentionnes dans le Parts No. ne sont pas fournis.
Telle ofine Parts No. werden night geliefent.

Les articles non mentionnes dans le Parts No, ne sont pas fournis.

Telle ohne Parts No. wenden nicht geliefent. Parts without Parts No. are not supplied.

Re- marks					7
Desti- nation 任 向	a F	ΣΣ >>		. <u></u>	4:KR-694
Description 部 品 名 / 規 格	MI-COM IC IC(VOLTAGE DETECTOR). ICCOP AMP X2) TRANSISTOR TRANSISTOR	TRANSISTOR FRANSISTOR FRANSISTOR TRANSISTOR TRANSISTOR	DIGITAL TRANSISTOR TRANSISTOR DIGITAL TRANSISTOR TRANSISTOR	ELECTRIC CIRCUIT MODULE ELECTRIC CIRCUIT MODULE	S.Singapore made
Parts No. 新品番号	UPD78044GF-075 S-80740AL NJM4580D-0 25C1740S(Q,R)	2SA1175(F,E) 2SA933S(Q,R) 7SC1740S(Q,R) 2SC2785(F,E) 2SC1845(F,E)	0741245S UN4112 DTC1246S UN4212	W02 - 1153 - 05 W02 - 1174 - 05	P.C. A. P.C. B.C.
New Parts	3012(11)	.,	3.50.		
Address (1)					
Ref. No. 参照番号	101 102 103 01 ,2	03 03 05 05 07 6	96 03 03		L.Scandrawa

# 1 22 2 2 3	## ## ## ## ## ## ## ## ## ## ## ## ##	BE ECTRO CRRAMIC CORRAMIC CORR	## ## / ## ## ## ## ## ## ## ## ## ## ##	t t t t t t t t t t t t t t t t t t t	no n
	99-3311-05 90-3311-05 91-0085-05 91-0085-05 91-0769-05 91-0769-05 91-0769-05 91-0769-05 91-0769-05 91-0759-05 91-0758-05 91-075	LECTRO ERAMMIC ERAMMIC ERAMMIC VIAR VIAR LECTRO ERAMIC LECTRO ERAMIC LECTRO LECTRO LECT	340° 6.3 340° 504° 0.0 0.020° N 0.010° N 0.020° J 0.020° J 0.030° 5.3 0.0560° J 0.0560° J 0.0560° J 0.060° J 0.		
m 44 % 00 m 0 4 m0 xx 00	99-92FM1H2233 91-3012-05 91-3012-05 91-3012-05 91-3011H321 90-3011H321 90-3011H321 91-301	YYLAR ELECTRO ELECTRO ERAMIC LECTRO FECTRO ERAMIC ERAMIC ELECTRO ELECTRO FECTRO FECTRO FECTRO	100220F J 1000 J		
20 00 00 00 00 00	092FR1HS63 664LR1F010 90-3225-05 91-0737-05 91-0737-05 91-0754-05 91-0754-05 90-3225-05 90-3225-05 90-0627-05 96-0628-05 96-0628-05 96-0632-05 96-0632-05	YVLAR LECTRO ERAMIC ERAMIC LECTRO LECTRO F	.0560F J .00F 5 70F 1 77PF J 60PF J .00F 1 00F 3 .0390F J		
ω 0 4 mo nω o o	90-3253-05 90-3224-05 90-3224-05 90-3224-05 90-227V1H393 90-0627-05 90-0628-05 90-0836-05 90-0836-05	LECTRO LECTRO LECTRO F LECTRO	UF 50 .7UF 16 0UF 35 0UF 35		
4 WO NO OO	E04LW1E470 78-0267-05 96-0492-05 96-0832-05 96-0832-05 96-0856-05 96-0856-05	LECTRO			
ma wa co	78-0267-05 96-0492-05 96-0832-05 96-0836-05 014NB2E221		251		
mo ww on	90-0492-05 90-0832-05 90-0856-05 014NB2E221	RESONATOR	(4.194MHZ)		
w	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	MULTI-COMP MULTI-COMP MULTI-COMP RD	100KX8 J 1/6 10KX3 J 1/6 10KX5 J 1/6 220 J 1/4 120 J 1/4	33333	-
wa oo	R10-5676-05	POTENTIOMETER	(100K X2)		
00	\$40-1064-05 \$40-1064-05	PUSH SWITCH PUSH SWITCH		TE	
00	T99-0547-05	ENCODER (INPUT	SELECTOR)		
	HSS104 1SS133 HZS6.2N(B2) RD6.2ES(B2) HZS2.7N(B2)	DIQDE DIQDE ZENER DIQDE ZENER DIQDE ZENER DIQDE			
and the state of	RD2.7ES(B2) HZS11N(B2) RD11ES(B2) HSS104 1SS133	ZENER DIØDE ZENER DIØDE ZENER DIØDE DIØDE			
	HSS104 155133 HSS104 155133 HSS104	0100E 0100E 0100E 0100E		TE XXX	 □ ⊢
	155133 HSS104 155133 11-MT-92GK UPD78043GF-073	DIQDE DIQDE DIQDE INDICATOR TURE MI-COM IC	0	YMXTE YM YM YM KPYMXE	YMXTE YM YM KPYMXR

KR-694/V5560/V6060 SPECIFICATIONS

For U.S.A and Canada (KR-694/V5560) Audio section

Rated power output at the STEREO operation

70 watts per channel minimum RMS, both channels driven at 8 Ω , from 20 Hz to 20,000 Hz with no more than 0.06 % total harmonic distortions. (FTC)

Power output at the Surround operation Front (1 kHz, 0.9 % T.H.D. at 8 Ω)
Total harmonic distortion (1 kHz, 8 Ω) 0.03 % at 50 W
Signal to noise ratio (IHF A)
PHONO (MM) 75 dB
CD, TAPE, VIDEO
Input sensitivity / impedance
PHONO (MM)
CD, TAPE, VIDEO 200 mV / 47 kΩ
Tone controls
BASS ± 10 dB (at 100 Hz)
TREBLE = 10 dB (at 10 kHz)
Loudness control at – 30 dB level + 6 dB (100 Hz)
Video continu

Video section

VIDEO inputs / outputs(Composite) 1 Vp - p / 75 Ω

FM Tuner section

Tuning frequency range Usable sensitivity (IHF)	87.5 MHz \sim 108 MHz 13.2 dBf (1.2 μ V at 75 Ω)
50 dB quieting sensitivity STEREO	41.2 dBf (3.2 μV at 75 Ω)
Total harmonic distortion at 1 kHz MONO	
Signal to noise ratio at 65 dBf (IHF) MONO	
STEREOSelectivity (IHF ± 400 kHz)	68 dB
Stereo separation (IHF at 1 kHz) Frequency response 30 Hz ~ 1	40 dB

AM Tuner section

Tuning frequency range	530 kHz ~ 1,700 kHz
Usable sensitivity	12 μV / (500 μV / m)
Total harmonic distortion	0.7 %
Signal to noise ratio	48 dB
Selectivity	30 dB
•	

General

Power consumption		3 A
AC outlet		
SWITCHED	. 2: (total 200 W,	1.6 A max.)
Dimensions	W:440 mm	(17-5/16")
		(5-5/8")
	D :334 mm	(13-1/8")
Weight (net)	9.5	kg (20.9 lb)

For other countries(KR-694/V5560) Audio section

Rated power output at the STEREO open	
(EIAJ) 1 kHz, 10 % T.H.D., at 8 Ω	100 W + 100 W
(IHF '66) from 20 Hz to 20 kHz,	
0.06% T.H.D., at 8 Ω	
Power output at the Surround operation	
Front (1 kHz, 0.9 % T.H.D. at 8 Ω)	
Center (1 kHz, 0.9 % T.H.D. at 8 Ω)	
Rear (1 kHz, 0.9 % T.H.D. at 8 Ω)	20 W + 20 W
Total harmonic distortion (1 kHz,	8 Ω) 0.03 % at 50 W
Signal to noise ratio (IHF'66)	
PHONO (MM)	
CD, TAPE, VIDEO	100 dB
Input sensitivity / impedance	
PHONO (MM)	
CD, TAPE, VIDEO	200 mV / 47kΩ
Tone controls	
BASS	
TREBLE	
Loudness control at - 30 dB level	+ 6 dB (100 Hz)

Video section

VIDEO inputs / outputs (Composite) 1 Vp - p / 75 Ω

FM Tuner section

Tuning frequency range	
STEREO	41.2 dBf (3.2 μV at 75 Ω)
Total harmonic distortion at 1 kHz	
MONO	0.6 %
STEREO	· ·
Signal to noise ratio at 65 dBf (IHF)	
MONO	75 dB
STEREO	68 dB
Selectivity (IHF ± 400 kHz)	50 dB
Stereo separation (IHF at 1 kHz)	
Frequency response 30 Hz ~ 1	

AM Tuner section

Tuning frequency range	
9 kHz	531 kHz ~ 1,602 kHz
10 kHz	530 kHz ~ 1,610 kHz
Usable sensitivity	12 µV / (500 µV / m)
Total harmonic distortion	0.7 %
Signal to noise ratio	48 dB
Selectivity	30 dB
*	

General

40,,0,4	
Power consumption	260 W
AC outlet	
SWITCHED	2: (total 200 W max.)
(Except for Australia)	
Dimensions	W:440 mm
	H :143 mm
	D :334 mm
Weight (net)	9.5 kg
•	_

Note: KENWOOD follows a policy of continuous advancements in development. For this reason specifications may be changed without notice.

KR-694/V5560/V6060 SPECIFICATIONS

U.S.A., Mexico and Canada(KR-V6060)
Audio section

Rated power output at the STEREO operation

100 watts per channel minimum RMS, both channels driven at 8 Ω , from 20 Hz to 20,000 Hz with no more than 0.06% total harmonic distortions. (FTC)

than 0.06% total harmonic distortions. (FTC)
Power output at the Surround operation
Front (1 kHz, 0.9% T.H.D. at 8 Ω)70 W + 70 W
Center (1 kHz, 0.9% T.H.D. at 8 Ω)70 W
Rear (1 kHz, 0.9% T.H.D. at 8 Ω)20 W + 20 W
Total harmonic distortion (1 kHz, 8 Ω)0.03% at 50 W
Signal to noise ratio (IHF A)
PHONO (MM)75 dB
CD, TAPE, VIDEO100 dB
Input sensitivity / impedance
PHONO (MM)2.5 mV / 47 kΩ
CD, TAPE, VIDEO200 mV / 47 kΩ
Tone controls
BASS±10 dB (at 100 Hz)
TREBLE
Loudness control at - 30 db level+ 8 dB (100 MZ)
Video section
VIDEO inputs / outputs(Composite) 1 Vp-p / 75 Ω
FM Tuner section
Tuning frequency range87.5 MHz~108 MHz
Usable sensitivity (IHF) 13.2 dBf (1.2 μ V at 75 Ω)
50 dB quieting sensitivity
STEREO41.2 dBf (3.2 μV at 75 Ω)
Total harmonic distortion at 1 kHz
MONO
STEREO0.7%
Signal to noise ratio at 65 dBf (IHF)
MONO
STEREO
Stereo separation (IHF at 1 kHz)40 dB
Frequency response30 Hz~15 kHz, +0.5 dB,- 3.0 dB
AM Tuner section
Tuning frequency range530 kHz~1,700 kHz
Usable sensitivity
Total harmonic distortion0.7 %
Signal to noise ratio48 dB
Selectivity30 dB
General
Power consumption3 A
AC outlet
SWITCHED2: (total 200 W, 1.6 A max.)
Dimensions
H: 143 mm (5-5/8")
D: 334 mm (13-1/8")

Other countries(KR-V6060)

Audio section

Audio Section
Rated power output at the STEREO operation
(EIAJ) 1 kHz, 10 % THD at 8 Ω135 W + 135 W
(IHF '66) from 20 Hz to 20 kHz,
0.06% T.H.D., at 8 Ω
Power output at the Surround operation
Front (1 kHz, 0.9% T.H.D. at 8 Ω)70 W + 70 W
Center (1 kHz, 0.9% T.H.D. at 8 Ω)70 W
Rear (1 kHz, 0.9% T.H.D. at 8 Ω) 20 W + 20 W
Total harmonic distortion (1 kHz, 8 Ω) 0.03% at 50 W
Signal to noise ratio (IHF'66)
PHONO (MM)75 dB
CD, TAPE, VIDEO100 dB
Input sensitivity / impedance
PHONO (MM)2.5 mV / 47 kΩ
CD, TAPE, VIDEO200 mV / 47kΩ
Tone controls
BASS±10 dB (at 100 Hz)
TREBLE±10 dB (at 10 kHz)
Loudness control at - 30 dB level+ 8 dB (100 Hz)
10.1
Video section
VIDEO inputs / outputs(Composite)1 Vp-p / 75 Ω
FM Tuner section
Tuning frequency range87.5 MHz~108 MHz
Usable sensitivity (IHF)13.2 dBf (1.2 μ V at 75 Ω)
50 dB quieting sensitivity
STEREO
Total harmonic distortion at 1 kHz
MONO
STEREO
Signal to noise ratio at 65 dBf (IHF) MONO75 dB
STEREO
Stereo separation (IHF at 1 kHz)
Frequency response30 Hz ~ 15 kHz, + 0.5 dB, - 3.0 dB
Frequency response30 112 ~ 13 k112, + 0.3 db, - 3.0 db
AM Tuner section
Am Tuner Scotton
Tuning frequency range
9 kHz531 kHz ~ 1,602 kHz
10 kHz530 kHz ~ 1,610 kHz
Usable sensitivity12 μV / (500 μV / m)
Total harmonic distortion
Signal to noise ratio
Selectivity
General
Power consumption260 W
AC outlet
SWITCHED2: (total 200 W max.)
(Except for Australia)
Dimensions W: 440 mm
H: 143 mm
D: 334 mm
Weight (not)

KR-694/V5560/V6060

KENWOOD CORPORATION

Alive Mitake, 2-5, 1-chome Shibuya, Shibuya-ku, Tokyo 150, Japan KENWOOD SERVICE CORPORATION PO. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745, U.S.A. KENWOOD ELECTRONICS CANADA INC. 6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8 KENWOOD ELECTRONICS LATIN AMERICA S.A. P.O. BOX 55-2791, Piso 6 Plaza Chase, Cl. 47 y Aguilino de la Guardia, Panama. Republic de Panama. TRIO-KENWOOD U.K. LIMITED Kenwood House, Owight Road, Watford, Herts, WD1 8EB, United Kingdom KENWOOD ELECTRONICS BENELUX N.V. Mecheisesteenweg 418 B-1930 Zaventem, Belgium KENWOOD ELECTRONICS DEUTSCHLAND GMBH Rembrücker Str. 15, 63150 Heusenstamm, Germany TRIO-KENWOOD FRANCE S.A. 13 Boulevard Ney, 75018 Paris, France KENWOOD ELECTRONICS ITALIA S.p.A. Via G. Sirtori, 7/9 20129 Milano, Italy KENWOOD ESPANA S.A. Bolivia, 239-08020 Barcelona, Spain KENWOOD ELECTRONICS AUSTRALIA PTY. LTD. (ACN 00: 499 07.4)
PO 80X 504, 8 Figtree Drive, Australia Centre, Homebush, NSW 2140, Australia
KENWOOD & LEE ELECTRONICS, LTD. Unit 3712:3724, Level 37 Tower 1, Metroplaza, 223 Hing Fong Road.
Kwai Fong N.T. Hong Kong
KENWOOD ELECTRONICS SINGAPORE PTE LTD
No. 1 Genting Lane #07-00, Singapore, 1334